



IS standard



GROWING TOGETHER

TR 137



PRODUCT DATA SHEET



Bias



R-1



A6



170

Technologies



Aramid Belted



Heavy Duty

Performance



High Load Capacity



Traction



Durability



Self-Cleaning




Stubble Resistance





Cut and Chip Resistance



TR 137

 TR 137 is BKT's most suitable tire for all harvesting operations. It ensures excellent traction in the fields even with high loads. The tire is available in different versions: the "aramid-belted" version provides better puncture resistance and protection against all typical damages of this application; the "HD" version provides extraordinary cut and chip resistance, and an extended tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 32"	24.5 - 32	DW 21 B	DW 20 B	622	1805	807	5343	STD	12	TL	159 A6
	24.5 - 32	DW 21 B	DW 20 B	622	1805	807	5343	STD	14	TL	163 A6
	30.5 L - 32	DH 27 B	DW 27 B	770	1865	831	5520	STD	12	TL	162 A6
	30.5 L - 32	DH 27 B	DW 27 B	770	1865	831	5520	STD	14	TL	164 A6
	30.5 L - 32	DH 27 B	DW 27 B	770	1865	831	5520	STD	16	TL	167 A6
	30.5 L - 32	DH 27 B	DW 27 B	770	1865	831	5520	AB	18	TL	170 A6
	30.5 L - 32	DH 27 B	DW 27 B	770	1865	831	5520	HD	18	TL	170 A6

STD: Standard - AB: Aramid Belted - HD: Heavy Duty



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference