IS standard

GROWING TOGETHER

TR 315

PRODUCT DATA SHEET

Bias

TR 315

TR 315 is suitable for lawn and garden, soil tillage and municipalities operations. It is ideal with implement machinery, trenchers and orchard harvesters. The TR 315 tire has a large contact area which provides excellent grip, great self-cleaning properties and outstanding stability in any condition.

Performance

Self-Cleaning

Stability

Traction

	Tire size	RIM Rec.	RIM Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
∅ 8″	**16 X 6.50 - 8**	5.375 I - 55 ; I - 70 ; I - 90	-	155	408	182	1183	STD	4	TL	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	155	408	182	1183	STD	6	TL	-
∅ 12″	**23 X 8.50 - 12**	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90	-	205	575	258	1668	STD	4	TL	-
	23 X 8.50 - 12	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90	-	205	575	258	1668	STD	6	TL	-
	23 X 10.50 - 12	8½ JA	7 JA	255	600	272	1840	STD	4	TL	-
	23 X 10.50 - 12	8½ JA	7 JA	255	600	272	1840	STD	6	TL	-
	23 X 10.50 - 12	8½ JA	7 JA	255	600	272	1840	STD	8	TL	-
	23 X 10.50 - 12	8½ JA	7 JA	255	600	272	1840	STD	10	TL	-
	23 X 10.50 - 12	8½ JA	7 JA	255	600	272	1840	STD	12	TL	-
	26 X 12.00 - 12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	STD	4	TL	-
	26 X 12.00 - 12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	STD	8	TL	-
	26 X 12.00 - 12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	SPL	10	TL	-
	26 X 12.00 - 12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	STD	10	TL	-
	26 X 12.00 - 12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	STD	12	TL	-

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference

Bias

Performance

Self-Cleaning

Stability

Traction

	Tire size	RIM Rec.	RIM Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
∅ 15"	**31 X 15.50 - 15**	13 LB	-	390	800	354	2320	STD	8	TL	-
	31 X 15.50 - 15	13 LB	-	390	800	354	2320	STD	10	TL	-
	31 X 15.50 - 15	13 LB	-	390	800	354	2320	STD	12	TL	-

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference

EN / 08-2024