



IS standard



GROWING TOGETHER

TR 390



PRODUCT DATA SHEET



Bias



R-3



A6



172

Performance




Durability




High Load Capacity



TR 390

 TR 390 is an agro-industrial tire suitable for sugar cane trailers and compactors. TR 390 features high load capacity and increased durability. Its "dual bead HD" version is particularly suitable for industrial tractors and transport operations using trailers, whereas its "dual bead HD special" version is ideal for heavy-duty service.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 26"	23.1 - 26	DW 20 B	-	595	1560	690	4545	DB HD	18	TL	161 A6
	23.1 - 26	DW 20 B	-	595	1560	690	4545	HD DB SPL	18	TL	161 A6
	23.1 - 26	DW 20 B	-	595	1560	690	4545	STD	8	TL	145 A6
	23.1 - 26	DW 20 B	-	595	1560	690	4545	STD	12	TL	153 A6
	23.1 - 26	DW 20 B	-	595	1560	690	4545	STD	16	TL	159 A6
	28 L - 26	DW 25 B	DW 23 B	714	1560	690	4545	DB HD	20	TL	172 A6
	28 L - 26	DW 25 B	DW 23 B	714	1560	690	4545	STD	12	TL	154 A6
	28 L - 26	DW 25 B	DW 23 B	714	1560	690	4545	DB	16	TL	160 A6

DB HD: Dual Bead Heavy Duty - HD DB SPL: Heavy Duty Dual Bead Special - STD: Standard - DB: Dual Bead



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference