



IS standard



GROWING TOGETHER

# TR 393



PRODUCT DATA SHEET



Bias



#### Technologies



Reinforced Carcass



Special Compound

#### Performance



Excellent flotation



Reduced Soil Compaction



Self-Cleaning



Traction



# TR 393

TR 393 has been specially designed for hay balers, spreaders and implement machinery on and off the road. The special tread design provides best flotation and self-cleaning properties in addition to a long service life. Thanks to its large contact area, TR 393 ensures excellent traction and minimizes soil compaction.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16.1"	16.5 L - 16.1 SL	W 14 C	W 14 CH	420	1025	461	2966	STD	6	TL	128 B
	21.5 L - 16.1 SL	W 18 CH	W 16 CH	546	1154	-	-	STD	10	TL	146 B

STD: Standard



Tolerances: O.D.  $\pm$  2% - S.W.  $\pm$  2% - RC  $\pm$  2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference