



IS standard



GROWING TOGETHER

TR 461



PRODUCT DATA SHEET



Bias



Performance

Cut and Chip
Resistance

Durability



Road Oriented



Stability



TR 461

TR 461 is a BKT pattern suitable for municipality and maintenance applications with tractors as well as for loading operations with telehandlers. The sidewall protection features particular resistance against cuts and bruises providing a longer life even on hard surfaces in addition to excellent stability.

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 18"	12.5/80 - 18	TL	12	129 A8	142 A8	STD	305	987	435	2902	W 9	11
	12.5/80 - 18	TL	18	138 A8	150 A8	STD	305	987	435	2902	W 9	11
Ø 24"	16.9 - 24	TL	14	151 A8		STD	440	1280	566	3763	DW 15 L	DW 14 L
	19.5 L - 24	TL	12	151 A8		STD	490	1310	578	3851	DW 16 L	-
	19.5 L - 24	TL	14	154 A8		STD	490	1310	578	3851	DW 16 L	-
	21 L - 24	TL	14	157 A8		STD	540	1385	607	4072	DW 18 L	-
Ø 28"	16.9 - 28	TL	14	154 A8		STD	440	1390	620	4087	DW 15 L	DW 14 L
Ø 34"	620/60 B 34	TL	-	175 A8		HD	615	1629	750	4930	DW 20 B	-

STD: Standard - HD: Heavy Duty



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling