



IS standard



GROWING TOGETHER

TR 882



PRODUCT DATA SHEET



Bias



149

Technologies



Heavy Duty



Special Compound



Aramid Belted

Performance



Cut and Chip Resistance



Durability



Stubble Resistance



Traction



TR 882

🇬🇧 TR 882 is a very versatile tire suitable for several applications and vehicles. It has been designed to fit implement machinery, hay harvesters/balers and sugar cane machinery. Engineered with a special compound to reduce damage, this tire features also great durability and traction in every field condition. TR 882 is also available as "aramid-belted", "HD" and "special" versions to meet specific end user requirements.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS		
		Rec.	Alt.									DW	FR
Ø 15.5"	400/60 - 15.5	AG 13.00	-	400	875	378	2605	AB	14	TL	132 A8	145 A8	
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	AB HD	18	TL	137 A8	149 A8	
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	HD	14	TL	132 A8	145 A8	
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	HD	18	TL	137 A8	149 A8	
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	SPL	14	TL	132 A8	145 A8	
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	SPL	18	TL	137 A8	149 A8	
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	STD	8	TL	122 A8	134 A8	
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	STD	14	TL	132 A8	145 A8	
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	STD	18	TL	137 A8	149 A8	
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	STD	18	TL	137 A8	149 A8	

AB: Aramid Belted - AB HD: Aramid Belted Heavy Duty - HD: Heavy Duty - SPL: Special - STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling