

AGMASTER



Excellent
Traction



Self
Cleaning

- Its 23°angle tread bars give superior traction and good resistance to wear abrasion and aging with good self-cleaning action



AGMASTER								TRA: R-1
Tire Size	P. R.	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity
			mm					Speed 40 km/h Kg
8.3-24	4	TT/TL	31.5	W7	993	211	160	630
	6						240	800
9.5-24	4	TT/TL	30.0	W7, W8, W8H	1048	241	140	750
	6						210	950
	8						280	1120
11.2-24	4	TT/TL	33.0	W9, W10, W10H	1103	284	130	850
	6						180	1060
	8						240	1250
11.2-28	4	TT/TL	30.0	W9, W10, W10H	1205	284	130	900
	6						180	1120
	8						240	1320
11.2-38	4	TT/TL	30.0	W10	1459	284	120	950
	6						180	1150
	8						240	1360
12.4-24	4	TT/TL	36.0	W11, W10, W10H	1159	315	110	950
	6						170	1215
	8						230	1450
12.4-28	4	TT/TL	36.0	W11, W10, W10H	1260	315	110	1000
	6						170	1285
	8						230	1550
12.4-38	4	TT/TL	36.0	W11, W11A, W10	1514	315	110	1180
	6						170	1500
	8						230	1800
13.6-24	4	TT/TL	36.5	W11, W12	1210	345	100	1030
	6						160	1360
	8						210	1550
13.6-28	4	TT/TL	36.5	W11, W12	1311	345	100	1120
	6						160	1450
	8						210	1650

AGMASTER								TRA: R-1
Tire Size	P. R.	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity
			mm				KPa	Speed 40 km/h Kg
13.6-38	4	TT/TL	36.5	W12, DW12A, W11	1565	345	100	1285
	6						160	1700
	8						210	1950
14.9-24	4	TT/TL	37.0	W12, W13	1265	378	100	1215
	6						140	1550
	8						180	1800
	12						300	2360
14.9-28	6	TT/TL	37.0	W12, W13	1367	378	140	1650
	8						180	1900
	10						220	2120
	12						260	2300
	14						290	2430
15.5-38	6	TT/TL	37.0	W14L, DW14A	1569	394	140	1800
	8						180	2060
16.9-24	6	TT/TL	39.0	W15L, W14L	1333	429	130	1750
	8						170	2060
	10						200	2240
16.9-30	6	TT/TL	39.0	DW15A, W15L, W14L, DW14A	1485	429	130	1900
	8						170	2240
	10						200	2500
	12						240	2725
	14						280	3000
18.4-30	6	TT/TL	40.0	DW16A, W15L, DW15A	1552	467	110	2120
	8						140	2430
	10						180	2800
	12						230	3250
	14						260	3450
18.4-34	6	TT/TL	40.0	DW16A, W16L, W15L, DW15A	1654	467	110	2240
	8						140	2575
	10						180	3000
	12						230	3450
	14						260	3750
18.4-38	6	TT/TL	40.0	W16A, W15L, DD16	1755	467	110	2360
	8						140	2725
	10						180	3250
	12						230	3650
	14						260	3875
20.8-38	8	TT/TL	41.9	W18A, DD18, DW18A	1834	528	130	3150
	10						160	3550
	12						200	4000
	14						240	4500
23.1-26	8	TT/TL	42.7	DW20B	1605	587	110	2900
	10	TT/TL	42.7	DW20B	1605	587	140	3250
	12	TT/TL	42.7	DW20B	1605	587	170	3650
	14	TT/TL	42.7	DW20B	1605	587	200	4000
	16	TT/TL	42.7	DW20B	1605	587	240	4500
	18PR+DUAL BEAD	TL	42.7	DW20A	1574	620	260	4125
24.5-32	10	TT/TL	43.4	DW21B, DH21, DW20B	1803	622	140	4000
	12						170	4500
	14						190	4750
	16						210	5000
30.5L-32	12	TT/TL	44.5	DH27B, DH27, DW27B	1819	775	140	4750
	14						150	5000
	16						180	5450
	18						210	6000