

AG-RADIAL



Field Protection



Durability



Self Cleaning



IF/VF Technology



Comfort

- Guaranteed true running and driving comfort up to 50 km/h
- Wide contact area for up to 4000 working hours
- More and wider lugs in ground and extended wear compound for durability
- Excellent driving on and off-the-road
- Good self-cleaning abilities due to special angle lugs
- Round shoulders for superior ground protection



AG-RADIAL 80/85/95 Series

TRA: R-1W

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ±2.5%	Rolling Circumference mm ±2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
280/85R20 (11.2R20)	112D	TL	42.0	10.00	986	282	446	2943	160	2575	1680	1380	1325	1290	1225	1175	1120
280/85R24 (11.2R24)	115D	TL	42.0	10.00	1080	285	494	3239	160	2795	1820	1495	1440	1400	1330	1275	1215
320/85R24 (12.4R24)	122A8/122B	TL	43.0	11.00	1139	322	520	3400	160	3450	2250	1845	1665	1605	1500	1500	-
340/85R24 (13.6R24)	125A8/125B	TL	45.0	12.00	1191	353	547	3558	160	3795	2475	2030	1830	1765	1650	1650	-
380/85R24 (14.9R24)	131A8/131B	TL	47.0	12.00	1273	382	566	3794	160	4485	2925	2400	2165	2090	1950	1950	-
420/85R24 (16.9R24)	137A8/137B	TL	48.0	15.00	1322	439	593	3935	160	5290	3450	2830	2550	2460	2300	2300	-
280/85R28 (11.2R28)	118A8/118B	TL	42.0	10.00	1182	283	540	3555	160	3035	1980	1620	1465	1410	1320	1320	-
320/85R28 (12.4R28)	124A8/124B	TL	43.0	11.00	1258	321	575	3776	160	3680	2400	1970	1775	1710	1600	1600	-
340/85R28 (13.6R28)	127A8/127B	TL	45.0	12.00	1308	353	598	3921	160	4025	2625	2150	1940	1870	1750	1750	-
380/85R28 (14.9R28)	133A8/133B	TL	47.0	13.00	1378	386	627	4124	160	4740	3090	2530	2290	2200	2060	2060	-
420/85R28 (16.9R28)	139A8/139B	TL	48.0	15.00	1438	439	637	4298	160	5590	3645	2990	2700	2600	2430	2430	-
380/85R30 (14.9R30)	135A8/135B	TL	46.0	13.00	1407	388	639	4218	160	5010	3270	2680	2420	2330	2180	2180	-
420/85R30 (16.9R30)	140A8/140B	TL	48.0	15.00	1483	439	674	4440	160	5750	3750	3075	2775	2675	2500	2500	-
420/90R30 (16.9R30)	142A8/142B	TL	48.0	13.00	1496	434	679	4478	160	6095	3975	3260	2940	2835	2650	2650	-
	147A8/147B								240	7070	4610	3780	3410	3290	3075	3075	-
460/85R30 (18.4R30)	145A8/145B	TL	50.0	16.00	1527	466	680	4566	160	6670	4350	3570	3220	3100	2900	2900	-
380/85R34 (14.9R34)	137A8/137B	TL	46.0	12.00	1487	389	681	4470	160	5290	3450	2830	2550	2460	2300	2300	-

AG-RADIAL 80/85/95 Series

TRA: R-1W

Tire Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius	Rolling Circumference	Inflation Pressure	Load Capacity Kg							
			mm		mm	mm	mm ± 2.5%	mm ± 2.5%	KPa	Static	10	20	25	30	40	50	65
420/85R34 (16.9R34)	142A8/142B	TL	48.0	15.00	1594	439	710	4784	160	6095	3975	3260	2940	2835	2650	2650	-
460/85R34 (18.4R34)	147A8/147B	TL	50.0	16.00	1649	470	743	4944	160	7070	4610	3780	3410	3290	3075	3075	-
	157A8/157B								320	9490	6190	5070	4580	4410	4125	4125	-
*1F580/80R34	177D/177A8	TL	53.0	DW20B	1792	597	814	5309	360	16790	9270	7880	7740	7590	7300	7300	7300
320/85R38 (12.4R38)	129A8/129B	TL	43.0	11.00	1496	310	720	4520	160	4255	2775	2275	2050	1980	1850	1850	-
380/80R38	142A8/142B	TL	46.0	12.00	1595	377	738	4803	240	6095	3975	3260	2940	2835	2650	2650	-
420/85R38 (16.9R38)	144A8/144B	TL	48.0	15.00	1667	439	752	5014	160	6440	4200	3440	3110	2995	2800	2800	-
460/85R38 (18.4R38)	149A8/149B	TL	50.0	16.00	1737	470	776	5207	160	7475	4875	4000	3610	3480	3250	3250	-
	151A8/151B								200	7935	5075	4240	3830	3690	3450	3450	-
520/85R38 (20.8R38)	155A8/155B	TL	51.0	18.00	1863	530	841	5589	160	8910	5810	4765	4300	4145	3875	3875	-
	175A8/175B								360	15870	10350	8490	7660	7380	6900	6900	-
650/85R38	173D/176A8	TL	60.0	20.00	2072	666	935	6192	240	14950	9750	7995	7700	7475	7100	6825	6500
460/85R42 (18.4R42)	151A8/151B	TL	50.0	16.00	1865	473	844	5611	160	7935	5175	4240	3830	3690	3450	3450	-
520/85R42 (20.8R42)	157A8/157B	TL	51.0	18.00	1958	530	875	5884	160	9490	6190	5070	4580	4410	4125	4125	-
	162A8/162B								240	10925	7125	5840	5270	5080	4750	4750	-
	165A8/165B								280	11845	7725	6335	5720	5510	5150	5150	-
380/90R46	149A8/149B	TL	47.0	12.00	1868	391	868	5633	240	7475	4875	4000	3610	3480	3250	3250	-
	159A8/159B								400	10060	6560	5380	4855	4680	4375	4375	-
VF380/90R46	173B/173D	TL	47.0	13.00	1868	395	868	5633	440	14950	7150	6760	6695	6630	6500	6500	6500
480/80R46 (18.4R46)	158A8/158B	TL	49.0	16.00	1971	490	905	5936	240	9775	6375	5225	4720	4550	4250	4250	-
520/85R46 (20.8R46)	158A8/158B	TL	51.0	18.00	2062	535	921	6205	160	9775	6375	5230	4720	4550	4250	4250	-
	174D/177A8								400	15500	10000	9000	8000	7750	7300	7100	6700
420/90R48	164A8/164B	TL	50.0	DW13	1975	418	-	-	380	11500	7500	6150	5550	5150	5000	5000	-
*380/90R50	158D/161A8	TL	44.0	DW12, DW13	1948	378	924	5872	360	9775	6375	5230	5040	4890	4625	4460	4250
480/80R50	159D/162A8	TL	49.0	DW16L	2028	475	-	-	240	10925	7125	5840	5270	5080	4750	4595	4375
	176A8/173B								500	16500	10600	9500	7750	7500	7100	6500	-
VF380/90R54	176D	TL	44.0	DW12, DW13	2038	391	937	6151	440	16330	7810	7380	7310	7240	7100	7100	7100

*: With Steel Belt

AG-RADIAL



Field Protection



Durability



Self Cleaning



IF/VF Technology



Comfort

- Guaranteed true running and driving comfort up to 50 km/h
- Wide contact area for up to 4000 working hours
- More and wider lugs in ground and extended wear compound for durability
- Excellent driving on and off-the-road
- Good self-cleaning abilities due to special angle lugs
- Round shoulders for superior ground protection



AG-RADIAL 70/75 Series

TRA: R-1W

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ±2.5%	Rolling Circumference mm ±2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
360/70R24	122A8/122B	TL	42.0	11.00	1135	354	518	3398	160	Static	10	20	25	30	40	50	65
360/70R24	122A8/122B	TL	42.0	11.00	1135	354	518	3398	160	3450	2250	1845	1665	1605	1500	1500	-
380/70R24	125A8/125B	TL	42.0	12.00	1198	384	533	3574	160	3795	2475	2030	1830	1765	1650	1650	-
420/70R24	130A8/130B	TL	45.0	13.00	1231	426	563	3675	160	4370	2850	2340	2110	2030	1900	1900	-
480/70R24	138A8/138B	TL	47.0	15.00	1314	488	580	3913	160	5430	3540	2900	2620	2525	2360	2360	-
	162A8/162B								400	10930	6890	5840	5040	4940	4750	4750	-
620/75R26	166A8/166B	TL	53.0	DW20B	1601	620	694	-	320	12190	7950	6520	5830	5670	5300	5300	-
360/70R28	125A8/125B	TL	42.0	11.00	1258	356	566	3777	160	3795	2475	2030	1830	1765	1650	1650	-
380/70R28	127D	TL	42.0	12.00	1304	382	589	3903	160	4025	2625	2150	2070	2010	1915	1840	1750
420/70R28	133A8/133B	TL	45.0	13.00	1350	414	597	4044	160	4740	3090	2530	2290	2200	2060	2060	-
480/70R28	140A8/140B	TL	47.0	15.00	1431	477	643	4279	160	5750	3750	3075	2775	2675	2500	2500	-
600/70R28	157D	TL	51.0	DW18L	1551	591	-	-	240	9490	6190	5070	4890	4740	4520	4330	4125
VF600/70R28	168D	TL	51.0	DW20B	1536	612	-	-	280	12880	7110	6050	5935	5820	5600	5600	5600
420/70R30	134A8/134B	TL	45.0	13.00	1384	422	615	4153	160	4875	3180	2610	2350	2270	2120	2120	-
480/70R30	141A8/141B	TL	47.0	15.00	1463	480	653	4382	160	5920	3860	3170	2860	2755	2575	2575	-
520/70R30	145A8/145B	TL	48.0	16.00	1528	522	692	4572	160	6670	4350	3570	3220	3100	2900	2900	-
	151A8/151B								240	7935	5175	4240	3830	3690	3450	3450	-
600/70R30	152A8/152B	TL	51.0	20.00	1610	586	716	4804	160	8165	5325	4370	3940	3800	3550	3550	-
	152D/155A8								160	8165	5325	4370	4210	4085	3875	3730	3550
VF600/70R30	170A8/170B	TL	51.0	DW20B, DW21B	1610	586	716	4804	240	13800	6600	6240	6180	6120	6000	6000	-
710/75R32	177A8/177B	TL	56.0	DW23B	1872	736	-	-	320	16790	10950	8980	8980	7810	7300	7300	-

AG-RADIAL 70/75 Series

TRA: R-1W

Tire Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius	Rolling Circumference	Inflation Pressure	Load Capacity Kg							
			mm		mm	mm	mm ± 2.5%	mm ± 2.5%	KPa	Static	10	20	25	30	40	50	65
480/70R34	143A8/143B	TL	47.0	15.00	1571	487	720	4717	160	6270	4090	3350	3025	2915	2725	2725	-
	149D								240	7475	4875	4000	3850	3740	3560	3410	3250
	155D								320	8910	5810	4770	4590	4460	4240	4070	3875
520/70R34	148A8/148B	TL	48.0	16.00	1639	530	739	4916	160	7245	4725	3875	3500	3370	3150	3150	-
600/70R34	160D/163A8	TL	51.0	20.00	1705	586	784	5107	240	10350	6750	5535	5330	5175	4875	4875	4500
*620/75R34	170D	TL	53.0	DW20B	1784	611	811	5326	320	13800	9000	7380	7100	6900	6500	6300	6000
*IF620/75R34	177D	TL	53.0	DW20B	1784	606	803	5303	320	-	-	-	-	-	-	-	7300
IF710/75R34 CFO	178B/178D	TL	48.0	DW25	1912	736	845	5604	240	21375	9525	8100	7950	7800	7500	7500	7500
480/70R38	145D	TL	47.0	15.00	1683	483	763	5062	160	6670	4350	3570	3435	3335	3175	3045	2900
520/70R38	150A8/150B	TL	48.0	16.00	1743	529	787	5238	160	7705	5025	4120	3720	3585	3350	3350	-
580/70R38	155A8/155B	TL	51.0	18.00	1822	580	811	5465	160	8910	5810	4770	4300	4145	3875	3875	-
	155D/158A8								160	8910	5810	4770	4590	4460	4250	4070	3875
	170A8/170B								280	13800	9000	7380	6660	6420	6000	6000	-
*580/70R38	180A8	TL	51.0	18.00	1822	580	-	-	460	18400	12000	9840	8880	8560	8000	8000	-
710/70R38	166D/169A8	TL	58.0	23.00	1950	741	863	5837	160	12190	7950	6520	6280	6095	5800	5565	5300
	177A8/177B								320	16790	10950	8980	8100	7810	7300	7300	-
	178D								340	17250	11250	9225	8890	8625	8210	7875	7500
*IF800/70R38	184B/184D	TL	60.0	27.00	2085	805	927	6190	240	20700	11430	9720	9540	9360	9000	9000	9000
580/70R42	158A8/158B	TL	51.0	18.00	1870	575	835	5625	160	9775	6375	5230	4720	4550	4250	4250	-
	176A8/176B								320	16330	10650	8730	7880	7600	7100	7100	-
620/70R42	160A8/160B	TL	52.0	20.00	1917	626	841	5762	160	10350	6750	5535	4995	4815	4500	4500	-
	166A8/166B								240	12190	7950	6520	5880	5670	5300	5300	-
710/70R42	173A8/173B	TL	58.0	23.00	2079	743	937	6234	240	14950	9750	7995	7215	6955	6500	6500	-
	173D/176A8								240	14950	9750	7995	7700	7475	7100	6825	6500
	176A8/176B								280	16330	10650	8733	7880	7600	7100	7100	-
	179D								320	17825	11625	9530	9180	8910	8485	8140	7750
710/75R42	175D/178A8	TL	62.0	23.00	2127	728	961	6356	240	15870	10350	8490	8175	7935	7500	7245	6900
	181D								320	18975	12375	10150	9775	9490	9030	8660	8250

*:With Steel Belt

AG-RADIAL



Longer
Tire Life



Excellent
Traction



Field
Protection



Self
Cleaning



High
Speed



IF/VF
Technology



Durability



Comfort

- 65 km/h capability
- Excellent mileage and durability
- More lugs in ground for enhanced traction
- High lugs and special anti-wear tread compound for extended tire lifetime
- Excellent driving on and off-the-road
- Good self-cleaning properties due to specially angled lugs
- Round shoulders for superior protection of grassland and turf



AG-RADIAL 60/65 Series

TRA: R-1W

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ±2.5%	Rolling Circumference mm ±2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
										Static	10	20	25	30	40	50	65
440/65R24	128D/131A8	TL	45.0	14.00	1190	437	530	3556	160	4140	2700	2210	2130	2070	1950	1890	1800
480/65R24	133D/136A8	TL	46.0	15.00	1224	469	541	3653	160	4740	3090	2535	2440	2370	2240	2160	2060
	140D/143A8								240	5750	3750	3075	2960	2875	2725	2625	2500
540/65R24	140D/143A8	TL	48.0	16.00	1316	540	585	3918	160	5750	3750	3075	2960	2875	2725	2625	2500
440/65R28	131D/134A8	TL	45.0	14.00	1288	439	579	3862	160	4485	2925	2400	2310	2240	2120	2050	1950
480/65R28	136D/139A8	TL	46.0	15.00	1336	466	593	4002	160	5150	3360	2755	2650	2575	2430	2350	2240
540/65R28	142D/145A8	TL	48.0	16.00	1424	533	631	4257	160	6095	3975	3260	3140	3050	2900	2780	2650
	149D/152A8								240	7475	4875	4000	3850	3735	3550	3410	3250
600/65R28	147D/150A8	TL	49.0	18.00	1486	593	652	4364	160	7070	4610	3780	3540	3535	3350	3230	3075
	154D/157A8								240	9490	5625	4610	4440	4310	4125	3940	3750
540/65R30	143D/146A8	TL	48.0	16.00	1477	535	653	4422	160	6900	4090	3350	3230	3130	3000	2860	2725
	150D/153A8								240	7705	5025	4120	3970	3850	3650	3520	3350
800/65R32 (30.5LR32)	172A8/172B	TL	57.0	25.00	1833	797	820	5460	240	14490	9450	7750	6990	6740	6300	6300	-
	178A8/178B								320	17250	11250	9225	8325	8025	7500	7500	-
IF800/65R32	181B/181D	TL	57.0	28.00	1833	797	820	5460	320	18975	10477	8910	8745	8580	8250	8250	8250
*IF900/60R32	185B/185D	TL	56.0	31.00	1910	891	855	5688	320	21275	11750	9990	9805	9620	9250	9250	9250
540/65R34	145D/148A8	TL	48.0	16.00	1581	539	716	4746	160	6670	4350	3570	3440	3335	3150	3045	2900
600/65R34	151D/154A8	TL	49.0	18.00	1665	607	750	4992	160	7935	5175	4240	4090	3970	3750	3620	3450
	157D/160A8								240	10350	6190	5070	4890	4740	4500	4330	4125
540/65R38	147D/150A8	TL	48.0	16.00	1682	539	759	5058	160	7070	4610	3780	3640	3540	3350	3230	3075
	153D/156A8								240	8395	5475	4490	4325	4200	4000	3830	3650
600/65R38	153D/156A8	TL	49.0	18.00	1768	604	796	5311	160	8395	5475	4490	4325	4200	4000	3830	3650

AG-RADIAL 60/65 Series										TRA: R-1W							
Tire Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius	Rolling Circumference	Inflation Pressure	Load Capacity Kg							
			mm		mm	mm	mm ± 2.5%	mm ± 2.5%	KPa	Static	10	20	25	30	40	50	65
650/65R38	157D/160A8	TL	51.0	20.00	1812	653	815	5439	160	9490	6190	5070	4890	4740	4500	4330	4125
	163D/166A8								240	11210	7310	6000	5780	5610	5300	5120	4875
*IF900/60R38 CFO	184B/184D	TL	63.0	31.00	2054	885	-	-	240	20700	11430	9720	9540	9360	9000	9000	9000
650/65R42	158D/161A8	TL	51.0	20.00	1921	651	865	5775	160	9775	6375	5230	5040	4890	4625	4460	4250
	165D/168A8								240	11845	7725	6330	6100	5920	5600	5410	5150

*.With Steel Belt