

AGRO-GRIP



Longer
Tire Life



Reduced Soil
Compaction



Fuel
Economy



Self
Cleaning



High
Speed



Comfort



High Loads
At Low Pressure

- High load capacity
- 65 km/h approval
- Excellent self-cleaning properties for safe driving
- Low ground compaction
- Especially suitable for transport on paved roads
- Low rolling resistance for fuel saving and comfortable ride
- Extended wear compound for enhanced tire lifetime



AGRO-GRIP

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ± 2.5%	Rolling Circumference mm ± 2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
										Static	10	20	25	30	40	50	65
500/50R17	149D	TL	15.0	16.00	932	503	418	2810	450	7475	5850	5360	5135	4910	4420	3930	3250
500/60R22.5	155D	TL	25.0	16.00	1170	506	528	3509	400	8910	6975	6390	6120	5850	5270	4690	3875
560/45R22.5	152D	TL	25.0	16.00	1072	538	480	3220	400	8165	6390	5860	5610	5360	4830	4295	3550
560/60R22.5	161D	TL	25.0	16.00	1256	562	559	3767	400	10640	8325	7630	7310	6980	6290	5600	4625
*560/60R22.5	164D	TL	25.0	16.00	1256	562	559	3767	440	11500	9000	8250	7900	7550	6800	6050	5000
	165D								500	11845	9270	8450	8140	7780	7000	6230	5150
600/50R22.5	159D	TL	25.0	20.00	1168	608	522	3507	400	10060	7875	7220	6910	6610	5950	5290	4375
*600/50R22.5	167D	TL	25.0	20.00	1168	608	522	3507	500	12535	9810	8990	8610	8230	7410	6595	5450
600/55R22.5	162D	TL	25.0	20.00	1214	610	537	3643	400	10925	8550	7840	7505	7170	6460	5750	4750
650/50R22.5	163D	TL	25.0	20.00	1208	654	532	3619	400	11210	8775	8040	7700	7360	6630	5900	4875
710/45R22.5	165D	TL	25.0	24.00	1202	718	538	3607	400	11845	9270	8500	8410	7780	7000	6230	5150
*710/45R22.5	165D	TL	25.0	24.00	1202	718	538	3607	400	11845	9270	8500	8140	7780	7000	6230	5150
600/55R26.5	165D	TL	25.0	20.00	1320	610	586	3966	400	11845	9270	8500	8140	7780	7000	6230	5150
620/55R26.5	166D	TL	25.0	20.00	1378	641	618	4142	400	12190	9540	8745	8370	8000	7210	6410	5300
650/55R26.5	169D	TL	25.0	20.00	1396	650	625	4196	400	13340	10440	9570	9160	8760	7890	7020	5800
*650/55R26.5	178D	TL	25.0	20.00	1396	650	625	4196	500	17250	13500	12375	11850	11325	10200	9075	7500
*710/50R26.5	170D	TL	25.0	24.00	1368	728	613	4113	400	13800	10800	9900	9480	9060	8160	7260	6000
750/45R26.5	170D	TL	25.0	24.00	1345	751	594	4044	400	13800	10800	9900	9480	9060	8160	7260	6000
*800/45R26.5	174D	TL	25.0	28.00	1390	800	625	4110	400	15410	12060	11050	10590	10100	9110	8110	6700

AGRO-GRIP

Tire Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius	Rolling Circumference	Inflation Pressure	Load Capacity Kg							
			mm							Speed Km/h							
										mm ± 2. 5%	mm ± 2. 5%	KPa	Static	10	20	25	30
*600/60R30.5	169D	TL	25.0	20.00	1487	624	673	4477	400	13340	10440	9570	9160	8760	7890	7020	5800
	173D								400	14950	11700	10725	10270	9815	8840	7865	6500
	179D								500	17825	13950	12790	12245	11700	10540	9380	7750
*650/65R30.5	176D	TL	25.0	20.00	1620	650	722	4873	400	16330	12780	11715	11220	10720	9660	8590	7100
*710/50R30.5	176D	TL	25.0	24.00	1470	719	662	4427	400	16330	12780	11715	11220	10720	9660	8590	7100
*750/60R30.5	181D	TL	25.0	24.00	1658	767	735	4986	400	18975	14850	13610	13035	12460	11220	9980	8250
*850/50R30.5	182D	TL	25.0	28.00	1610	862	718	4844	400	19550	15300	14025	13430	12835	11560	10285	8500

*:With Steel Belt