

AG RADIAL SPECIAL



Longer
Tire Life



Field
Protection



Excellent
Traction



IF/VF
Technology

- Adopted with super wear-resistant and anti-aging tread design, the service life of tires is increased.
- The design of pattern block angle is more scientific with wide driving surface, super traction and good mud-discharge.
- Lower R-1 studs with 40 mm tread depth and an adapted tire shoulder make it in this dimension to the ideal tire for nutrient application on grassland or other sensitive soils.
- IF technology provide resilience and soil-friendly.



AG RADIAL SPECIAL

TRA: R-1

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ± 2.5%	Rolling Circumference mm ± 2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
380/85R26 (14.9R26)	127A8/127B	TL	38.0	12.00	1295	378	592	3857	160	4025	2625	2150	1940	1870	1750	1750	-
620/75R26 (23.1R26)	166A8/166B	TL	45.0	20.00	1605	641	722	4778	320	12190	7950	6520	5880	5670	5300	5300	-
750/65R26	158A8/158B	TL	46.0	25.00	1600	761	710	4761	160	9775	6375	5230	4720	4530	4250	4250	-
	166A8/166B								240	12190	7950	6520	5880	5670	5300	5300	-
	172A8/172B								320	14490	9450	7750	6990	6740	6300	6300	-
420/85R28 (16.9R28)	139A8/139B	TL	39.0	15.00	1403	448	623	4206	160	5590	3645	2990	2700	2600	2430	2430	-
380/85R30 (14.9R30)	135A8/135B	TL	38.0	12.00	1407	380	635	4218	160	5010	3270	2680	2420	2330	2180	2180	-
650/75R32 (24.5R32)	172A8/172B	TL	48.0	20.00	1796	658	810	5362	320	14490	9450	7750	6990	6740	6300	6300	-
*650/75R32 (*24.5R32)	180A8/180B	TL	48.0	20.00	1796	658	810	5362	500	18400	12000	9840	8880	8560	8000	8000	-
*IF1050/50R32	185B/185D	TL	40.0	36.00	1863	1038	833	5686	240	21275	11750	9990	9805	9620	9250	9250	9250
420/80R46	151A8/151B	TL	40.0	13.00	1848	398	849	5272	240	7935	5175	4240	3830	3690	3450	3450	-
320/90R50 (12.4R50)	150A8/150B	TL	36.0	10.00	1828	305	854	5527	360	7705	5025	4120	3720	3585	3350	3350	-
12.4R54	133A8/133B	TL	36.0	11.00	1921	315	907	5811	210	4740	4740	2090	2530	2290	2060	2060	-
320/90R54 (12.4R54)	156A8/156B	TL	36.0	10.00	1926	318	910	5826	440	9200	6000	4920	4440	4280	4000	4000	-

*:With Steel Belt