



- Optimized steer and trailer pattern for long haul application with fuel efficiency
- High volume pattern design guarantees long mileage and fuel efficiency
- Straight simple rib pattern improves efficient water evacuation for excellent wet traction and handling
- Four waved grooves aids in stone rejection performance
- Improved close shoulder reduces the irregular wear throughout the duration of tread-life



● : Recommendable ● : Available

AS578

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
● 11.00R20	J/18	152/149K	16.0	8.0	1085	293	3550	7825	930	135	3250	7165	930	135
● 9.5R17.5	H/16	143/141J	13.0	6.75	842	240	2725	6005	875	128	2575	5675	875	128
● 10R22.5	H/16	144/142M	15.0	7.50	254	1019	2800	6175	900	130	2650	5840	900	130
● 11R22.5	H/16	148/145L	14.2	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
● 12R22.5	J/18	152/149L	15.5	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
● 295/60R22.5	J/18	150/147L	15.0	9.00	926	292	3350	7390	900	131	3075	6780	900	131
● 245/70R22.5	J/18	142/139K	15.0	7.50	915	248	2650	5840	900	131	2430	5360	900	131
● 255/70R22.5	H/16	140/137M	14.5	7.50	930	255	2500	5510	830	120	2300	5070	830	120
● 275/70R22.5	H/16	144/141M	15.5	8.25	958	276	2800	6175	830	120	2575	5675	830	120
● 315/70R22.5	L/20	156/150L	13.5	9.00	1014	312	4000	8820	900	130	3350	7390	900	130
● 275/80R22.5	J/18	149/146L	14.0	8.25	1012	276	3250	7165	900	130	3000	6610	900	130
● 295/80R22.5	H/16	150/147M	15.0	9.00	1044	298	3350	7390	830	120	3075	6780	830	120
● 295/80R22.5	J/18	152/149M	15.0	9.00	1044	298	3550	7830	900	131	3250	7160	900	131
● 315/80R22.5	J/18	154/151M(156/153L)	15.0	9.00	1076	312	3750	8270	830	120	3450	7610	830	120

● Made in China