



Long Haul



- Super value tyre for long haul application
- Stone ejector platforms prevent tread damage from stone drilling
- Four main straight grooves guarantee excellent drainage ability and even wear resulting in long tread life



AT167

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11.00R20	J/18	152/149K	15.0	8.0	1085	293	3550	7825	930	135	3250	7165	930	135
265/70R19.5	H/16	140/138M	13.0	7.50	867	262	2500	5510	775	112	2360	5200	775	112
265/70R19.5	J/18	143/141J	13.0	7.50	867	262	2725	6005	850	123	2575	5675	850	123
11R22.5	H/16	148/145M	14.2	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149L	14.5	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
255/70R22.5	H/16	140/137M	14.0	7.50	930	255	2500	5510	830	120	2300	5070	830	120
275/70R22.5	H/16	148/145M	14.0	8.25	958	276	3150	6940	900	130	2900	6395	900	130
295/75R22.5	G/14	144/141L	14.2	9.00	1020	298	2800	6175	760	110	2575	5675	760	110
295/80R22.5	J/18	152/149M	14.0	9.00	1050	298	3550	7830	900	131	3250	7610	900	131
315/80R22.5	J/18	154/151M(156/153L)	14.5	9.00	1076	312	3750	8270	830	120	3450	7610	830	120
11R24.5	H/16	149/146L	14.2	8.25	1104	279	3250	7160	830	120	3000	6610	830	120

03

GOLDEN CROWN

TYRE CATALOGUE