



- Wide and deep tread enhance driving stability and mileage on all kinds of roads
- Special tread compound and carcass help to guarantee long tyre life and better retreadability
- Zig-zag main grooves provide superb traction level



●: Recommendable

AZ534/AZ534+

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
● 225/80R17.5(AZ534)	H/16	123/122L	15.8	6.75	805	226	1550	3415	700	102	1500	3305	700	102
● 225/90R17.5(AZ534)	H/16	127/125L	15.8	6.75	851	226	1750	3860	700	102	1650	3640	700	102
● 245/70R19.5(AZ534)	G/14	133/131M	16.0	7.50	839	248	2060	4540	760	110	1950	4300	760	110
● 245/70R19.5(AZ534)	H/16	136/134M	16.0	7.50	839	248	2240	4940	830	120	2120	4675	830	120
● 265/70R19.5(AZ534)	H/16	140/138M	16.0	7.50	867	262	2500	5510	775	112	2360	5200	775	112
● 265/70R19.5(AZ534)	J/18	143/141J	16.0	7.50	867	262	2725	6005	850	123	2575	5675	850	123
● 11R22.5(AZ534+)	G/14	144/142L	17.0	8.25	1054	279	2800	6175	720	105	2650	5840	720	105
● 11R22.5(AZ534+)	H/16	148/145L	17.0	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
● 275/80R22.5(AZ534+)	H/16	149/146L	18.0	8.25	1012	276	3250	7165	850	123	3000	6610	850	123
● 295/80R22.5(AZ534+)	H/16	150/147M	18.0	9.00	1044	298	3350	7390	830	120	3075	6780	830	120
● 295/80R22.5(AZ534+)	J/18	152/149M	18.0	9.00	1044	298	3550	7830	900	131	3250	7160	900	131

● Made in China