



- Premium five-rib tread with various pitches to provide quiet and comfortable riding
- Stone ejection design reduces stone retention and casing penetration
- Computer aided casing design helps improve footprint for better mileage performance



● : Recommendable    ● : Available

# AZ670

| Size              | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure |       |       |       |      |       |       |       |
|-------------------|---------|---------------|------------------|--------------|-----------------------|--------------------|-----------------------------------------------|-------|-------|-------|------|-------|-------|-------|
|                   |         |               |                  |              |                       |                    | Single                                        |       |       |       | Dual |       |       |       |
|                   |         |               |                  |              |                       |                    | (kg)                                          | (lbs) | (kPa) | (psi) | (kg) | (lbs) | (kPa) | (psi) |
| 🇨🇳 🇹🇭 11R22.5     | G/14    | 144/142M      | 16.0             | 8.25         | 1054                  | 279                | 2800                                          | 6175  | 720   | 105   | 2650 | 5840  | 720   | 105   |
| 🇨🇳 🇹🇭 11R22.5     | H/16    | 148/145M      | 16.0             | 8.25         | 1054                  | 279                | 3150                                          | 6940  | 850   | 123   | 2900 | 6390  | 850   | 123   |
| 🇨🇳 12R22.5        | J/18    | 152/149L      | 16.0             | 9.00         | 1085                  | 300                | 3550                                          | 7830  | 930   | 135   | 3250 | 7160  | 930   | 135   |
| 🇨🇳 255/70R22.5    | H/16    | 140/137M      | 15.0             | 7.50         | 930                   | 255                | 2500                                          | 5510  | 830   | 120   | 2300 | 5070  | 830   | 120   |
| 🇨🇳 🇹🇭 295/80R22.5 | H/16    | 150/147M      | 16.0             | 9.00         | 1044                  | 298                | 3350                                          | 7390  | 830   | 120   | 3075 | 6780  | 830   | 120   |
| 🇨🇳 🇹🇭 295/80R22.5 | J/18    | 152/149M      | 16.0             | 9.00         | 1044                  | 298                | 3550                                          | 7830  | 900   | 131   | 3250 | 7160  | 900   | 131   |

🇨🇳 Made in China    🇹🇭 Made in Thailand