

BACKTRACK RADIAL SUPREME



Reinforced
Shoulder



Excellent
Traction



Durability



Stability



Cut & Chip
Resistance

- Strong tread lugs for severe applications
- High traction on hard and abrasive surfaces
- Reinforced lug base and middle for severe applications
- Durable tire
- Robust and reinforced shoulders for advanced stability and cut resistance
- Special bead protection



BACKTRACK RADIAL SUPREME

TRA: R-4

Tire Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius mm ± 2.5%	Rolling Circumference mm ± 2.5%	Inflation Pressure KPa	Load Capacity Kg						
			mm							Static	10	20	25	30	40	50
280/80R18 (10.5/80R18)	132A8/132B	TL	28.0	W9	914	288	415	2736	400	4600	2500	2180	2120	2080	2000	2000
340/80R18 (12.5/80R18)	143A8/143B	TL	30.0	11.00	996	353	442	2973	400	6270	3405	2970	2890	2830	2725	2725
400/70R18 (405/70R18)	147A8/147B	TL	33.0	13.00	1020	408	453	3048	400	7070	3840	3350	3260	3200	3075	3075
280/80R20 (10.5/80R20)	133A8/133B	TL	28.0	W9	967	285	432	2901	400	4740	2575	2245	2180	2140	2060	2060
340/80R20 (12.5/80R20)	144A8/144B	TL	30.0	11.00	1053	356	474	3151	400	6440	3500	3050	2970	2910	2800	2800
380/75R20 (14.5R20)	148A8/148B	TL	33.0	W12	1088	386	483	3249	400	7245	3940	3430	3340	3275	3150	3150
400/70R20 (16.0R20)	149A8/149B	TL	33.0	13.00	1072	408	476	3203	400	7475	4060	3540	3445	3380	3250	3250
*400/70R20 (16.0R20)	149A8/149B	TL	33.0	13.00	1072	408	476	3203	400	7475	4060	3540	3445	3380	3250	3250
*400/70R24 (16.0R24)	152A8/152B	TL	33.0	13.00	1172	407	525	3515	400	8165	4440	3870	3760	3690	3550	3550
440/80R24 (16.9R24)	161A8/161B	TL	36.0	DW13, DW14L	1312	457	582	3923	400	10640	5780	5040	4900	4810	4625	4625
460/70R24 (17.5LR24)	159A8/159B	TL	36.0	DW15L	1247	468	554	3732	400	10060	5470	4770	4640	4550	4375	4375
500/70R24 (19.5LR24)	164A8/164B	TL	36.0	DW16L	1317	505	584	3938	400	11500	6250	5450	5300	5200	5000	5000
540/70R24	168A8/168B	TL	36.0	DW16L, DW18L	1364	536	-	-	400	12880	7000	6345	6170	5820	5600	5600
480/80R26 (18.4R26)	160A8/160B	TL	36.0	DW15L	1412	497	628	4103	320	10350	5625	4905	4770	4680	4500	4500
440/80R28 (16.9R28)	156A8/156B 163A8/163B	TL	36.0	DW13, DW14L	1416	456	637	4247	320 400	9200 11213	5000 6094	4360 5310	4240 5168	4160 5070	4000 4875	4000 4875

*:With Steel Belt

BACKTRACK RADIAL SUPREME

TRA: R-4

Tire Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius mm ± 2.5%	Rolling Circumference mm ± 2.5%	Inflation Pressure KPa	Load Capacity	
			mm							Speed 90 km/h	Kg
495/70R24	155G	TL	36	DW16L	1294	495	597	3914	400	3850	