



CB538

Size	TRA Code	Ply Rating	LUG #	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure		T/TL
								(kg)	(#/lb)	
8.3-24	R-1	C/6	18	30.0	W7	995	210	810	240	TT
8.3-24	R-1	D/8	18	30.0	W7	995	210	950	300	TT
9.5-24	R-1	D/8	19	33.0	W8	1050	240	1110	280	TT
11.2-24	R-1	B/4	17	35.0	W10	1105	285	750	120	TT
11.2-24	R-1	C/6	17	35.0	W10	1105	285	950	180	TT
11.2-24	R-1	D/8	17	35.0	W10	1105	285	1150	240	TT
12.4-24	R-1	B/4	17	36.0	W11	1160	315	850	110	TT
12.4-24	R-1	C/6	17	36.0	W11	1160	315	1090	170	TT
12.4-24	R-1	D/8	17	36.0	W11	1160	315	1295	220	TT
14.3-24	R-1	B/4	17	38.0	W13	1265	378	1210	100	TT/TL
14.3-24	R-1	C/6	17	38.0	W13	1265	378	1360	140	TT/TL
14.3-24	R-1	D/8	17	38.0	W13	1265	378	1600	180	TT/TL
16.3-24	R-1	C/6	19	39.0	W15L	1335	430	1725	130	TT/TL
11.2-28	R-1	B/4	18	35.0	W10	1205	285	800	120	TT
12.4-28	R-1	T/6	19	36.0	W11	1260	315	1150	170	TT
14.3-28	R-1	C/6	18	38.0	W13	1365	378	1610	140	TT
14.3-28	R-1	D/8	18	38.0	W13	1365	378	1880	180	TT
14.3-28	R-1	E/10	18	38.0	W13	1365	378	2120	230	TT
16.3-28	R-1	C/6	19	39.0	W15L	1435	430	1840	130	TT
16.3-28	R-1	D/8	19	39.0	W15L	1435	430	2175	170	TT
14.3-30	R-1	D/8	21	38.0	W13	1415	378	1940	180	TT
14.3-30	R-1	E/10	21	38.0	W13	1415	378	2190	230	TT
16.3-30	R-1	C/6	20	39.0	W15L	1485	430	1900	130	TT
16.3-30	R-1	D/8	20	39.0	W15L	1485	430	2245	170	TT
16.3-30	R-1	F/12	20	39.0	W15L	1485	430	2730	240	TT
18.4-30	R-1	C/6	19	38.0	W16L	1550	467	2120	110	TT
18.4-30	R-1	D/8	19	38.0	W16L	1550	467	2415	140	TT
18.4-30	R-1	F/12	19	38.0	W16L	1550	467	3180	230	TT
11-32	R-1	C/6	20	36.0	W10	1450	296	1080	160	TT
24.5-32	R-1	F/12		43.0	DW21	1805	622	4000	170	TL
24.5-32	R-1	G/14		43.0	DW21	1805	622	4375	190	TL
30.5L-32	R-1	F/12		43.0	DW27	1845	775	4745	140	TL
30.5L-32	R-1	H/16		43.0	DW27	1845	775	5370	170	TL
16.3-34	R-1	D/8	23	39.0	W15L	1585	430	2380	170	TT
16.3-34	R-1	E/10	23	39.0	W15L	1585	430	2605	200	TT
18.4-34	R-1	C/6		40.0	W16L	1655	467	2250	110	TT
18.4-34	R-1	F/12		40.0	W16L	1655	467	3375	230	TT
11.2-38	R-1	B/4	22	30.0	W10	1465	285	950	120	TT/TL
12-38	R-1	D/8	22	36.0	W11	1514	315	1600	220	TT
12.4-38	R-1	B/4	22	36.0	W11	1565	315	1165	110	TT
12.4-38	R-1	D/8	22	36.0	W11	1565	315	1750	230	TT
13.5-38	R-1	C/6	23	36.0	W12	1565	345	1660	160	TT
13.5-38	R-1	E/10	23	36.0	W12	1565	345	2215	250	TT
14.3-38	R-1	C/6	23	38.0	W13	1615	378	1870	140	TT
14.3-38	R-1	D/8	23	38.0	W13	1615	378	2180	180	TT
15.5-38	R-1	B/4	22	37.5	W14L	1570	395	1280	100	TT
15.5-38	R-1	C/6	22	37.5	W14L	1570	395	1765	140	TT
16.3-38	R-1	C/6	28	39.0	W15L	1685	430	2130	130	TT
16.3-38	R-1	D/8	28	39.0	W15L	1685	430	2520	170	TT
18.4-38	R-1	C/6	23	40.0	W16L	1755	467	2380	110	TT
18.4-38	R-1	D/8	23	40.0	W16L	1755	467	2715	140	TT
20.5-38	R-1	D/8	22	40.0	W18L	1835	528	3090	130	TT
20.5-38	R-1	F/12	22	40.0	W18L	1835	528	4000	200	TT
24.5-32	R-1	F/12	22	43.0	DW21A	1805	620	4000	178	TL
24.5-32	R-1	G/14	22	43.0	DW21A	1805	620	4375	190	TL
30.5L-32	R-1	F/12	22	43.0	DW21A	1845	775	4250	140	TL
30.5L-32	R-1	H/16	22	43.0	DW21A	1845	775	5000	180	TL
230/95-48	R-1	H/16		32.0	W7	1656	229	2000	320	TL