



- Continuous central design ensures driving stability and smooth ride
- The central siped zig-zag rib ensures even wear and grip on wet and muddy surface
- Enhanced durability over rough road with good on-road performance



● : Recommendable
● : Available

CB981

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
● 6.50R16	G/14	110/105J	10.0	5.50F	750	185	1060	2335	670	97	925	2040	670	97
● 7.00R16	H/16	118/114J	14.0	5.50F	785	200	1320	2910	770	112	1180	2600	770	112
● 7.50R16	G/14	122/118L	16.0	6.00G	815	215	1500	3305	770	112	1320	2910	770	112
● 8.25R16	G/14	128/126L	16.5	6.50H	865	235	1800	3970	670	97	1700	3750	670	97
● 8.25R16	H/16	128/124L	16.5	6.50H	865	235	1800	3970	770	112	1600	3525	770	112
● 8.25R20	H/16	139/137K	17.0	6.5	974	236	2430	5360	930	135	2300	5070	930	135
● 9.00R20	H/16	144/142K	18.0	7.0	1019	259	2800	6175	900	130	2650	5840	900	130
● 10.00R20	H/16	146/143K	19.5	7.5	1054	278	3000	6610	830	120	2725	6005	830	120
● 10.00R20	J/18	149/146J	19.5	7.5	1054	278	3250	7160	930	135	3000	6610	930	135
● 11.00R20	J/18	152/149J	20.5	8.0	1085	293	3550	7825	930	135	3250	7165	930	135
● 12.00R20	J/18	154/151K	20.5	8.5	1125	315	3750	8270	830	120	3450	7610	830	120
● 11R22.5	G/14	144/142L	19.6	8.25	1065	279	2800	6175	720	105	2650	5840	720	105
● 11R22.5	H/16	148/145L	19.6	8.25	1065	279	3150	6940	850	123	2900	6390	850	123

● Made in China ● Made in Thailand