

FORKLIFT TYRES



CL402(S)

Resilent

Size	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load (kg)										Tire Weight (kg)	
					Empty/10km/h		10mph/16km/h		Empty/25km/h		Depth/Depth	Other Vehicles		Empty/25km/h		
					Load	Steer	Load	Steer	Load	Steer		Empty/6km/h	Empty/10km/h	Empty/25km/h		
5.00-8	25	3,00D	460	128	1255	965	1145	880	1060	815	1305	1060	960	815	17.7	
	25	3,25I	460	128	1360	1045	1235	950	1150	885	1415	1150	1045	885	18.0	
	25	3,75	460	128	1570	1205	1430	1100	1325	1020	1630	1325	1200	1020	18.1	
6.00-9	25	4,00E	523	146	1975	1520	1805	1390	1675	1290	2065	1675	1520	1290	26.5	
6.50-10	25	5,00F	574	156	2715	2090	2485	1910	2310	1775	2840	2310	2095	1775	33.6	
	25	5,50F	574	156	2985	2300	2735	2100	2540	1950	3125	2540	2305	1950	34.0	
7.00-12	25	5,00S	655	160	3105	2390	2835	2180	2635	2025	3240	2635	2390	2025	45.5	
7.00-15	25	5,50	730	180	3700	2845	3375	2595	3135	2410	3855	3135	2845	2410	57.0	
	25	6,00	730	180	4035	3105	3680	2830	3420	2630	4205	3420	3105	2630	58.0	
8.25-15	30	5,50	820	207	4305	3310	3925	3020	3640	2800	4480	3640	3305	2800	86.5	
	30	6,50	820	207	5085	3910	4640	3570	4310	3315	5304	4310	3910	3315	87.0	