

FORKLIFT TYRES



CL619

Industrial Service-Forklift

Size	TBA Code	Pg Rating	Service Index	Standard Rim	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity (kg)	Cold Inflation Pressure (kPa)	TT/TL
5,00-8	-	10	-	3,50D	12,0	470	137	1150	1000	TT
6,00-9	-	8	-	4,00E	13,0	540	160	1315	690	TT
	-	10	-	4,00E	13,0	540	160	1505	860	TT
6,50-10	-	10	-	5,00F	13,0	590	175	1655	790	TT
7,00-12	-	12	-	5,00S	15,0	676	190	2375	860	TT
7,00-15	-	12	-	5,5	15,0	750	200	2870	860	TT
7,50-15	-	12	-	6,0	17,0	780	215	3075	790	TT
8,25-15	-	14	-	6,5	16,0	840	235	3775	830	TT
	-	16	-	6,5	16,0	840	235	4330	900	TT
18x7-8	-	16	-	4,33R	14,0	173	465	1640	1000	TT
21x8-9	-	14	-	6,00E	15,5	535	200	2040	1000	TT
23x9-10	-	18	-	6,50F	16,0	595	225	3160	1050	TT
	-	14	-	7,0	13,0	710	220	3050	970	TT
28x9-15	-	16	-	7,0	13,0	710	220	3115	1000	TT
250-15	-	16	-	7,5	21,5	735	250	3865	930	TT
	-	18	-	8,0	22,0	840	300	5530	830	TT
300-15	-	20	-	8,0	22,0	840	300	5940	930	TT