

FORKLIFT TYRES



CL621

Industrial Service-Forklift

Size	TRA Code	PL Rating	Service Index	Standard Rim	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity (kg)	Cold Inflation Pressure (kPa)	TT/TL
5,00-8	-	10	-	3,50D	11,0	470	137	1150	1000	TT
6,00-9	-	10	-	4,00E	12,5	540	160	1505	860	TT
7,00-9	-	10	-	5,00S	10,0	590	190	1995	860	TT
6,50-10	-	10	-	5,00F	12,0	590	175	1655	790	TT
7,00-12	-	12	-	5,00S	13,0	676	190	2375	860	TT
8,25-12	-	12	-	6,5	19,0	765	235	3060	720	TT
6,00-15	-	10+	-	4,50E	14,0	705	170	2185	830	TT
8,25-15	-	14	-	6,5	16,0	840	235	3775	830	TT
9,00-16	-	14	-	6,50H	16,0	890	255	4495	760	TT
8,25-20	-	14	-	6,5	15,0	974	235	3865	830	TT
9,00-20	-	16	-	7,0	17	1018	259	4715	860	TT
18x7-8	-	14	-	4,33R	16,0	173	465	1440	900	TT
23x9-10	-	18	-	6,50F	14,0	595	225	3160	1050	TT
27x10-12	-	14	-	8,00G	14,0	690	255	3210	720	TT
28x9-15	-	14	-	7,0	16,0	710	220	3050	970	TT
250-15	-	16	-	7,5	21,0	735	250	3865	930	TT
300-15	-	18+	-	8,0	23,0	840	300	5530	830	TT