

OFF-THE-ROAD TYRES-BIAS



Classic no-directional tread design formulated with Cut resistance compound
Together with a robust duty nylon carcass makes it capable of withstanding cuts in all tough service conditions

CL728

Loader / Earthmover / Grader

Size	TBA Code	Ply Rating	Standard Rim	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity (kg)	Cold Inflation Pressure (kPa)	TT/TL
23,5-25	E-3	16	19,50/2,5	33,0	1615	595	6150	225	TT/TL
	L-3	16	19,50/2,5	33,0	1615	595	9500	300	TT/TL
	E-3	20	19,50/2,5	33,0	1615	595	7300	300	TT/TL
	L-3	20	19,50/2,5	33,0	1615	595	10900	375	TT/TL
	E-3	24	19,50/2,5	33,0	1615	595	8000	350	TT/TL
	L-3	24	19,50/2,5	33,0	1615	595	12500	475	TT/TL
29,5-25	E-3	28	25,00/3,5	50,0	1875	750	11500	325	TL
	L-3	28	25,00/3,5	50,0	1875	750	17500	425	TL
	L-3	34	25,00/3,5	50,0	1875	750	20000	525	TL