



- This tyre delivers outstanding traction, long even wear and advanced casing design to ensure durability
- An extra wide, self cleaning and full depth tread design provides improved water evacuation, lateral stability
- A strong shoulder block ensures a flat even wear on all types of application with shallow lug grooves on shoulder to minimize shoulder heel and toe
- Stone ejection groove design provides a more durable casing life for retreadability by minimizing damage to the casing



CM333

Size	LR/PR	Service Index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure			
							Single (KG)	Single (KPA)	Dual (KG)	Dual (KPA)
11.00R20	J/18	152/149K	20.0	8.00	1085	293	3550	930	3250	930
12.00R20	J/18	154/151K	21.0	8.50	1125	315	3750	830	3450	830
11R22.5	H/16	148/145L	19.6	8.25	1065	279	3150	850	2900	850
12R22.5	H/16	150/147L	20.0	9.00	1085	300	3350	830	3075	830
12R22.5	J/18	152/149L	20.0	9.00	1085	300	3550	930	3250	930
315/80R22.5	J/18	154/151M(156/150L)	20.6	9.00	1082	312	3750	830	3450	830