



- Wide tread designed for improved mileage
- Large block design helps enhance handling and traction on all-season highway conditions
- Special rubber compound provides high mileage and long tread life



CM993

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure			
							Single (KG)	Single (KPA)	Dual (KG)	Dual (KPA)
9.00R20	H/16	144/142K	17.0	7.00	1019	259	2800	900	2650	900
10.00R20	J/18	149/146J	18.0	7.50	1054	278	3250	930	3000	930
11.00R20	J/18	152/149K	19.0	8.00	1085	293	3550	930	3250	930
12.00R20	J/18	154/151K	20.0	8.50	1125	315	3750	830	3450	830
11R22.5	H/16	148/145L	20.6	8.25	1065	279	3150	850	2900	850
12R22.5	H/16	150/147L	20.6	9.00	1085	300	3350	830	3075	830
12R22.5	J/18	152/149L	20.6	9.00	1085	300	3550	930	3250	930
295/80R22.5	H/16	150/147M	20.6	9.00	1050	298	3350	830	3075	830
295/80R22.5	J/18	152/149M	20.6	9.00	1050	298	3550	900	3250	900
315/80R22.5	J/18	154/151M(156/150L)	20.6	9.00	1082	312	3750	830	3450	830