



CR832

Size	Ply	Service Index	Tread Depth (mm)	Standard Rim	Inflated Profile		Max. Load Capacity at Cold Inflation Pressure			
					Section Width	Overall Diameter	Single		Dual	
					(mm)	(mm)	(kg)	(kPa)	(kg)	(kPa)
6.00-14LT	8	95/90L	7.5	4 1/2J	170	680	690	420	600	420
6.00-14LT	8	95/90L	9.5	4 1/2J	170	680	690	420	600	420
6.00-15LT	10	101/97L	8.0	4.50E	170	705	825	530	730	530
6.50-15LT	10	106/101L	8.5	4.50E	180	730	950	530	825	530
7.00-15LT	10	109/105L	10.0	5.50F	200	750	1030	530	935	530
7.00-15LT	12	113/109L	10.0	5.50F	200	750	1150	630	1030	630
6.50-16LT	10	107/103L	10.0	5.50F	185	750	975	530	875	530
6.50-16LT	12	110/105L	10.0	5.50F	185	750	1060	630	925	630
7.00-16LT	10	111/106L	10.5	5.50F	200	775	1090	530	950	530
7.00-16LT	12	115/110L	10.5	5.50F	200	775	1215	630	1060	630
7.00-16LT	14	118/114L	10.5	5.50F	200	775	1320	730	1180	730
7.50-16LT	10	116/112L	10.0	6.00G	215	805	1250	530	1120	530
7.50-16LT	12	120/116L	10.0	6.00G	215	805	1400	630	1250	630
7.50-16LT	12+	120/116L	10.0	6.00G	215	805	1400	630	1250	630
7.50-16LT	14	122/118G	10.0	6.00G	215	805	1500	730	1320	730