



URBAN



- Four rib tread pattern provides uniform wear and excellent traction on wet and dry road.
- Deep and wide tread enhances mileage for exceptionally long tyre life
- Reinforced shoulder and steel sidewall help deliver long casing life and retreadability
- Sidewall protector ribs help resist sidewall damage from turning, backing and braking when used in urban neighborhoods.
- Cool-running compound delivers low rolling resistance meaning more fuel efficiency



● : Recommendable

CR906/CR906II

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure					
							Single			Dual		
							(kg)	(lbs)	(kPa) (psi)	(kg)	(lbs)	(kPa) (psi)
● 11R22.5(CR906II)	H/16	144/142J	20.0	8.25	1065	279	2800	6175	720 105	2650	5840	720 105
● 11R22.5(CR906II)	J/18	148/145J	20.0	8.25	1065	279	3150	6940	850 123	2900	6390	850 123
● 255/70R22.5(CR906)	H/16	140/137J	17.5	7.50	936	255	2500	5510	830 120	2300	5070	830 120
● 275/70R22.5(CR906II)	H/16	148/145J(152/148F)	20.0	8.25	964	276	3150	6940	900 130	2900	6395	900 130
● 275/80R22.5(CR906)	H/16	140/146J	19.0	8.25	1012	276	3250	7165	850 123	3000	6610	850 123
● 295/80R22.5(CR906)	H/16	150/147M	19.0	9.00	1050	298	3350	7390	830 120	3075	6780	830 120
● 295/80R22.5(CR906)	J/18	152/149L	19.0	9.00	1050	298	3550	7830	900 131	3250	7160	900 131

● Made in China ● Made in Thailand