



MIXED SERVICE ON & OFF



CR926 / CR926B / CR926D

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
6.50R16(CR926)	F/12	110/105L	9.5	5.50F	750	185	1060	2335	670	97	925	2040	670	97
7.00R16(CR926)	G/14	118/114M	11.0	5.50F	775	200	1320	2910	770	112	1180	2600	770	112
7.50R16(CR926)	G/14	122/118L	12.0	6.00G	805	215	1500	3305	770	112	1320	2910	770	112
7.50R20(CR926)	G/14	130/128L	14.0	6.0	935	215	1900	4190	830	120	1800	3970	830	120
8.25R16(CR926)	G/14	126/122L	14.0	6.50H	855	235	1700	3750	670	97	1500	3305	670	97
8.25R16(CR926)Reinforced	G/14	128/126L	14.0	6.50H	855	235	1800	3970	670	97	1700	3750	670	97
8.25R20(CR926)	H/16	139/137L	15.0	6.5	974	236	2430	5360	930	135	2300	5070	930	135
9.00R20(CR926)	H/16	144/142K	15.5	7.0	1019	259	2800	6175	900	130	2650	5840	900	130
10.00R20(CR926)	H/16	146/143K	16.0	7.5	1054	278	3000	6610	830	120	2725	6005	830	120
10.00R20(CR926)	J/18	149/146J	16.0	7.5	1054	278	3250	7160	930	135	3000	6610	930	135
11.00R20(CR926)	J/18	152/149K	16.0	8.0	1085	293	3550	7825	930	135	3250	7160	930	135
12.00R20(CR926)	J/18	154/151K	17.5	8.5	1125	315	3750	8270	830	120	3450	7610	830	120
12.00R20(CR926)	L/20	156/153J	17.5	8.5	1125	315	4000	8820	900	131	3650	8050	900	131
12.00R24(CR926)	L/20	160/157K	16.0	8.5	1226	315	4500	9920	900	131	4125	9090	900	131
12.00R24(CR926B)	L/20	160/157K	19.0	8.5	1226	315	4500	9920	900	131	4125	9090	900	131
325/95R24(CR926B)	M/22	162/160K	19.0	9.00	1228	325	4750	10470	850	123	4500	9920	850	123
11R22.5(CR926D)	G/14	144/142M	16.8	8.25	1054	279	2800	6175	720	105	2650	5840	720	105
11R22.5(CR926D)	H/16	148/145M	16.8	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
11R22.5(CR926D)	J/18	149/146L	16.8	8.25	1054	279	3250	7160	930	135	3000	6610	930	135
12R22.5(CR926)	J/18	152/149L	16.0	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
13R22.5(CR926)	J/18	156/151K	16.0	9.75	1124	320	4000	8820	875	128	3450	7610	875	128
255/70R22.5(CR926D)	H/16	140/137L	14.2	7.50	930	255	2500	5510	830	120	2300	5070	830	120
295/80R22.5(CR926D)	H/16	150/147M	16.0	9.00	1044	298	3350	7390	830	120	3075	6780	830	120
295/80R22.5(CR926D)	J/18	152/149L	16.0	9.00	1044	298	3550	7830	900	131	3250	7160	900	131
315/80R22.5(CR926B)	J/18	154/151M(156/150L)	16.5	9.00	1076	312	3750	8270	830	120	3450	7610	830	120
315/80R22.5(CR926B)	L/20	157/154K	16.5	9.00	1076	312	4125	9090	900	130	3750	8270	900	130
11R24.5(CR926D)	G/14	146/143L	16.8	8.25	1104	279	3000	6610	720	105	2725	6005	720	105
11R24.5(CR926D)	H/16	149/146L	16.8	8.25	1104	279	3250	7160	830	120	3000	6610	830	120
12R24.5(CR926D)	J/18	154/151L	17.0	9.00	1147	300	3750	8270	930	135	3450	7610	930	135

● Made in China ● Made in Thailand

- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



● : Recommendable ● : Available