



- Tread pattern provides extended even wear and offers excellent wet traction
- Advanced compound promotes mileage before removal for long tyre life



• : Recommendable

CR950

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
• 7.50R16	G/14	122/118L	12.0	6.00G	805	215	1500	3305	770	112	1320	2910	770	112
• 8.25R16	H/16	128/124L	14.0	6.50H	855	235	1800	3970	770	112	1600	3525	770	112
• 7.50R20	G/14	130/128L	13.0	6.0	935	215	1900	4190	830	120	1800	3970	830	120
• 8.25R20	H/16	139/137K	14.0	6.5	974	236	2430	5360	930	135	2300	5070	930	135
• 8.5R17.5	F/12	121/120L	12.0	6.00	802	215	1450	3200	625	91	1400	3090	625	91
• 9.5R17.5	G/14	129/127L	13.0	6.75	842	240	1850	4080	750	109	1750	3860	750	109
• 9.5R17.5	H/16	143/141J	13.0	6.75	842	240	2725	6005	875	128	2575	5675	875	128
• 215/75R17.5	H/16	135/133J	13.0	6.00	767	211	2180	4805	850	123	2060	4540	850	123
• 8R22.5	G/14	130/128M	13.5	6.00	935	203	1900	4190	830	120	1800	3970	830	120
• 9R22.5	G/14	136/134M	14.0	6.75	974	229	2240	4940	830	120	2120	4675	830	120
• 10R22.5	H/16	144/142M	15.0	7.50	1019	254	2800	6175	900	130	2650	5840	900	130

• Made in China • Made in Thailand