



- Five ribs with four wide, straight grooves for precise handling and outstanding traction
- Solid shoulder helps to minimize shoulder wear and improve cost per mile
- Advanced cool-running tread compounds reduces heat generated and increases irregular wear resistance resulting in higher mileage



CR966

Size	LR / PR	Service Index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure			
							Single (KG)	Single (KPA)	Dual (KG)	Dual (KPA)
11R22.5	H/16	148/145M	15.0	8.25	1054	279	3150	850	2900	850
12R22.5	H/16	150/147L	15.5	9.00	1085	300	3350	830	3075	830
12R22.5	J/18	152/149L	15.5	9.00	1085	300	3550	930	3250	930
295/60R22.5	J/18	150/147L	15.0	9.00	926	292	3350	900	3075	900
315/60R22.5	J/18	152/148M	15.0	9.75	950	313	3550	900	315	900
295/80R22.5	H/16	150/147M	15.0	9.00	1044	298	3350	830	3075	830
295/80R22.5	J/18	152/149M	15.0	9.00	1044	298	3550	900	325	900
315/80R22.5	J/18	154/151M(156/150L)	16.0	9.00	1076	312	3750	830	3450	830
385/55R22.5	L/20	160K/158L	15.0	12.25	996	386	4500	900		