

DEFENDER



Field Protection



Reduced Soil Compaction

- Row crop tires with rounded shoulders for every kind of cultivation, harvesting and spraying operation
- Minimum damage to crops even in narrow spaced plantations
- Strong radial casing for optimum ground pressure distribution and low ground compaction lowers damage to soil and increases crop yield



DEFENDER

TRA: R-1

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ±2.5%	Rolling Circumference mm ±2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
230/95R32 (9.5R32)	128A8/128B	TL	33.0	7.00, W7, W8	1240	236	585	3742	400	4140	2700	2210	2000	1930	1800	1800	-
270/95R32 (11.2R32)	136A8/136B 136D	TL	35.0	9.00, W9, W8, W10	1319	284	620	3975	400	5150	3360	2755	2485	2400	2240	2240	-
									400	5150	3360	2755	2655	2575	2450	2350	2240
230/95R36 (9.5R36)	128A8/128B	TL	33.0	7.00, W7, W8	1345	229	636	4078	360	4140	2700	2210	2000	1930	1800	1800	-
270/95R36 (11.2R36)	137A8/137B 139A8/139B	TL	35.0	9.00, W9, W8, W10	1422	283	663	4291	360	5290	3450	2830	2550	2460	2300	2300	-
									400	5590	3645	2990	2700	2600	2430	2430	-
270/95R38 (11.2R38)	140A8/140B 140D	TL	35.0	9.00, W9, W8, W10	1474	285	691	4450	400	5750	3750	3075	2775	2675	2500	2500	-
									400	5750	3750	3075	2960	2875	2740	2625	2500
230/95R40 (9.5R40)	135A8/135B	TL	33.0	7.00, W7, W8	1454	228	662	4395	400	5010	3270	2680	2420	2330	2180	2180	-
230/95R42 (9.5R42)	133A8/133B	TL	33.0	7.00, W7, W8	1497	228	684	4527	400	4740	3090	2530	2290	2200	2060	2060	-
270/95R42 (11.2R42)	140A8/140B 140D	TL	35.0	9.00, W9, W8, W10	1580	283	744	4774	360	5750	3750	3075	2775	2675	2500	2500	-
									360	5750	3750	3075	2960	2875	2740	2625	2500
320/80R42	141A8/141B	TL	35.0	10.00, W10, W9, W11	1567	315	730	4771	320	5920	3860	3170	2860	2755	2575	2575	-
230/95R44 (9.5R44)	134A8/134B 134D	TL	33.0	7.00, W7, W8	1547	229	735	4679	400	4875	3180	2610	2350	2268	2120	2120	-
									400	4875	3180	2610	2510	2440	2320	2230	2120
270/95R44 (11.2R44)	142A8/142B 142D	TL	35.0	9.00, W9, W8, W10	1627	279	768	4917	400	6095	3975	3260	2940	2835	2650	2650	-
									400	6095	3975	3260	3140	3050	2900	2780	2650
270/95R46 (11.2R46)	143A8/143B	TL	35.0	9.00, W9, W8, W10	1677	282	798	5066	400	6270	4090	3350	3025	2915	2725	2725	-
300/95R46 (12.4R46)	148A8/148B 148D	TL	37.0	9.00, W9, W10, W11	1732	305	815	5233	400	7245	4725	3875	3500	3370	3150	3150	-
									400	7245	4725	3875	3730	3620	3450	3310	3150

DEFENDER										TRA: R-1												
Tire Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius	Rolling Circumference	Inflation Pressure	Load Capacity Kg												
			mm							mm	mm	mm ±2.5%	mm ±2.5%	KPa	Static	10	20	25	30	40	50	65
320/90R46 (12.4R46)	148A8/148B	TL	37.0	10.00, W10, W9, W11	1737	315	810	5248	360	7245	4725	3875	3500	3370	3150	3150	-					
340/85R46	150A8/150B	TL	41.0	11.00, W12, W11	1770	352	835	5345	360	7705	5025	4120	3720	3585	3350	3350	-					
230/95R48 (9.5R48)	136A8/136B  136D	TL	33.0	7.00, W7, W8	1647	230	780	4984	400 400	5150 5150	3360 3360	2755 2755	2485 2654	2396 2575	2240 2450	2240 2350	- 2240					
270/95R48 (11.2R48)	144A8/144B  144D	TL	35.0	9.00, W9, W8, W10	1734	286	821	5243	400 400	6440 6440	4200 4200	3440 3320	3110 3220	3000 3065	2800 2940	2800 2800	- 2800					
340/85R48	152A8/152B  152D	TL	37.0	11.00, W12, W11	1803	339	850	5463	400 400	8165 8165	5325 5325	4370 4210	3940 4080	3800 3890	3550 3730	3550 3550	- 3550					
300/95R52 (12.4R52)	151A8/151B	TL	37.0	9.00, W9, W10, W11	1889	305	895	5712	400	7935	5175	4240	3830	3690	3450	3450	-					
270/95R54 (11.2R54)	146D/149A8	TL	35.0	W9	1880	277	-	-	400	6900	4500	3690	3330	3210	3250	3000	3000					