

# DNR (S)

17

(TRA CODE:E-3/L-3)

DIRT N ROCK (S TREAD)

Tires for large loaders and scrapers. The massive cross lugs and wide ground contact tread provide excellent traction, wear resistance and cut resistance. Better resistance to heat build-up than E-4 tires.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		T/ @50km/h		L/ @10km/h	
							mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa
WIDE BASE TIRE														
29.5-25	22	—	△	38.0	1.50	25.00/3.5	800	31.5	1900	74.8	10000	250	15000	325
	28	—	△								11500	325	17500	425
	34	—	△								—	—	20000	525
29.5-29	22	—	△	38.0	1.50	25.00/3.5	800	31.5	2002	78.8	10600	250	16000	325
	28	—	△								12150	325	19000	425
	32	—	△								13200	375	20600	500
	34	—	△								14000	400	21200	525
29.5-35	28	—	△	38.0	1.50	25.00/3.5	800	31.5	2103	82.8	13600	325	20600	425
	32	—	△								14500	375	21800	475
	34	—	△								15000	400	23000	525
	38	—	△								16000	450	24800	600
33.25-35	32	—	△	42.5	1.67	27.00/3.5	845	33.25	2242	88.28	16000	325	25750	450
	36	—	△								17500	375	27250	500
	38	—	△								18000	400	28000	525
	44	—	△								19900	475	30200	600
33.5-33	32	—	△	42.5	1.67	28.00/4.0	851	33.5	2242	88.28	16500	325	25750	425
	38	—	△								18500	400	29000	525
	44	—	△								—	—	30750	600

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
							Overall Width		Overall Diameter		T/ @50km/h		L/ @10km/h	
		TT	TL	mm	inch		mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa
37.25-35	30	—	△	46.5	1.83	31.00/4.0	1001	39.4	2357	92.8	17500	275	28000	375
	36	—	△								19500	325	30750	450
	42	—	△								21800	400	33500	525
37.5-33	36	—	△	6.5	1.83	32.00/4.5	1024	40.3	2357	92.8	20000	325	31500	450
	42	—	△								22400	400	34500	525
	44	—	△								23200	425	35400	550
75/30-33	36	—	△	38.0	1.50	25.00	780	30.7	1905	75.0	—	—	22450	620
	42	—	△								—	—	23900	690
	48	—	△								—	—	25300	760
98/40-41	48	—	△	46.5	1.83	32.00	993	39.1	2357	92.8	—	—	36040	620
	60	—	△								—	—	40600	760