



- Super value tyre for mixed service application
- Aggressive lug design with larger blocks at tread center provides excellent traction
- Open shoulder tread design improves self-cleaning capacity for ease of maintenance



EZ175/EZ175A

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
10.00R20	J/18	149/146D	20.0	7.5	1065	278	3250	7160	930	135	3000	6610	930	135
11.00R20	J/18	152/149D	20.0	8.0	1096	293	3550	7825	930	135	3250	7165	930	135
12.00R20	J/18	154/151F	21.0	8.5	1125	315	3750	8270	830	120	3450	7610	830	120
11R22.5	H/16	148/145J	19.5	8.25	1065	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149F	19.5	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
295/80R22.5	J/18	152/149J	20.0	9.00	1050	298	3550	7830	900	131	3250	7160	900	131
315/80R22.5(EZ175A)	L/20	157/154K	16.0	9.00	1076	312	4125	9090	900	130	3750	8270	900	130