

F302



Field Protection



High Flotation



Durability



High Loads At Low Pressure



Self Cleaning

- Tubeless flotation tire offers good self-cleaning characteristics
- Suitable for all agricultural implements especially for towed vehicles
- Offers high load capacity at low inflation pressures thus preventing damages to fields and crops
- Tire for on and off-the-road agricultural service on trailers, tractors and large implements
- It offers enhanced durability due to the strong casing construction and compounds used

F302

Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Inflation Pressure KPa	Load Capacity Kg			
										Free Rolling Speed Km/h			
										10	25	30	40
10.0/75-15.3	10	TL	10.0	9.00	760	274	343	2227	520	2170	1845	1735	1550
	14								710	2660	2260	2130	1900
	18								710	3300	2810	2640	2360
	22								840	3920	3330	3130	2800
10.5/80-18	14	TL	11.0	W9	885	275	395	2593	700	3300	2810	2640	2360
11.5/80-15.3	10	TL	10.0	9.00	844	297	370	2473	460	2730	2320	2180	1950
	14								650	3400	2890	2720	2430
	18								600	3920	3330	3130	2800
12.5/80-15.3	14	TL	12.0	9.00	885	312	387	2593	430	3710	3150	2970	2650
	18								550	4200	3570	3360	3000
12.5/80-18	12	TL	11.0	W9	965	308	432	2877	500	3710	3150	2970	2650
13.0/65-18	16	TL	11.0	11.00	890	336	398	2608	675	3920	3330	3135	2800
13.0/75-16	12	TL	12.0	11.00	890	340	396	2726	380	3300	2810	2640	2360