

FORESTRY FLOTATION X1



- The high flotation forestry tires, with large ground contact area, low-pressure ratio on the ground and less damage to soil and sapling.
- Tread bars at certain angle give good self-cleaning capacity, excellent traction and slide slippage-proof.
- Its carcass design with steel belt protection gives the best resistance to punctures.
- Deep tread design and cut-resistant tread compound give extended tire life.



OEM FITMENT



FORESTRY FLOTATION X1									TRA: HF-2/LS-1	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity	
									Speed 40km/h Inflation KPa	Load kg
*650/65-26.5	20	TT	35.0	20.00	1476	658	-	-	500	6700
*710/45-26.5	20	TT/TL	30.0	24.00	1326	727	616	4095	500	5600
*750/55-26.5	20	TT/TL	35.0	24.00	1476	758	685	4565	500	7300
	24								600	8500

FORESTRY FLOTATION X1									TRA:LS-2	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity	
									Speed 40km/h Inflation KPa	Load kg
*780/50-28.5	24	TL	35.0	26.00	1528	793	-	-	600	8500

* : With Steel Belt