

FORESTRY FLOTATION X- II



- The tire and the anti-skid chains track are closely matched. The unique groove straight line design in the tread crown improves the traction performance of the tire.
- The smooth curve of shoulder provides strong support for anti-skid chains track, and the stress on the running surface of the tire is well-distributed. The stress damage of track to tire is declined.
- With excellent traction, it can be applied to heavy forestry machines.



Better Fit
with Tracks



Longer
Tire Life



Deep Tread



Reduced Soil
Compaction



Excellent
Traction



Self
Cleaning

OEM FITMENT



FORESTRY FLOTATION X- II									TRA: LS-2	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity	
									Speed 40km/h	
									Inflation KPa	Load kg
 *710/40-24.5	20	TT/TL	35	AG24.00	1228	686	-	-	500	4875
 *710/45-26.5	20	TT/TL	35	AG24.00	1347	702	-	-	500	5600
	24								600	6500
*710/55-28.5	24	TT/TL	35	AG24.00	1510	734	-	-	600	8000
*750/55-26.5	24	TT/TL	33	AG24.00	1490	762	663	4329	600	8500
*780/50-28.5	24	TT/TL	35	AG26.00	1514	790	697	4571	600	8500
*800/40-26.5	20	TT/TL	35	AG28.00	1350	786	625	4065	500	6000

*:With Steel Belt