

FLOTATION RADIAL/FLOTATION RADIAL-1



High Speed



High Loads
At Low Pressure



Reduced Soil
Compaction



Self
Cleaning

- High load capacity
- 65 km/h approval
- Good self-cleaning properties
- Suitable for grassland
- Low ground compaction
- Low rolling resistance
- Suitable for on/off-the-road agricultural service on tractors, trailers and agricultural implements



FLOTATION RADIAL

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ± 2.5%	Rolling Circumference mm ± 2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
500/50R17	145D	TL	15.0	16.00	925	497	412	2780	400	6670	5220	4785	4580	4380	3940	3510	2900
	149D									7475	5850	5360	5135	4910	4420	3930	3250
500/60R22.5	155D	TL	26.0	16.00	1186	483	537	3558	400	8910	6975	6390	6120	5850	5270	4670	3875
560/45R22.5	152D	TL	25.0	16.00	1085	523	486	3266	400	8165	6390	5860	5610	5360	4830	4295	3550
600/50R22.5	159D	TL	26.0	20.00	1185	580	536	3556	400	10060	7875	7220	6910	6605	5950	5290	4375
	163D								500	11210	8775	8040	7700	7360	6630	5900	4875
710/45R22.5	165D	TL	26.0	24.00	1189	678	530	3567	400	11845	9270	8500	8140	7780	7000	6230	5150
600/55R26.5	165D	TL	26.0	20.00	1361	587	608	4046	400	11845	9270	8500	8140	7780	7000	6230	5150
710/50R26.5	170D	TL	26.0	24.00	1342	678	596	4034	400	13800	10800	9900	9480	9060	8160	7260	6000

FLOTATION RADIAL-1

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ± 2.5%	Rolling Circumference mm ± 2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
560/60R22.5	161D	TL	20.0	16.00	1277	522	570	3837	400	10640	8235	7630	7310	6980	6290	5600	4625
560/60R22.5	165D	TL	20.0	16.00	1277	522	570	3837	500	11845	9270	8450	8140	7780	7000	6230	5150