

FLOTATION TRACTION



Field Protection



High Loads At Low Pressure



Durability



Self Cleaning

- Tubeless flotation tire offers good self-cleaning characteristics
- Offers high load capacity at low inflation pressures thus preventing damages to fields and crops
- It offers enhanced durability due to the strong casing construction and compounds used
- Tire for on and off-the-road agricultural service on trailers, tractors and large implements



FLOTATION TRACTION

TRA: I-3

Tire Size	P. R.	Load Index Speed Symbol		TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius	Rolling Circumference	Inflation Pressure	Load Capacity Kg							
		Speed Km/h																	
		Free Rolling										Drive Wheel							
		Free Rolling	Drive Wheel											mm	mm	mm	mm±2.5%	mm±2.5%	KPa
*500/45-20	18	-	160A8	TL	25.0	16.00	965	485	-	-	600	-	-	-	-	6300	5350	4500	4050
500/60-22.5	12	157A8	145A8	TL	35.0	16.00DC	1170	500	513	3503	240	5780	4910	4125	3710	4060	3450	2900	2610
	16	163A8	151A8	TL							320	6830	5800	4875	4390	4830	4110	3450	3110
NEW 600/40-22.5	16	-	148A8	TL	35.0	20.00	1092	592	486	3258	280	-	-	-	-	4410	3750	3150	2840
*600/40-22.5	18	-	169A8	TL	35.0	20.00	1092	592	486	3258	600	-	-	-	-	8120	6910	5800	5230

*.With Steel Belt