

GENESIS



Longer
Tire Life



Excellent
Traction



Field
Protection



Stability



Reduced Soil
Compaction



Self
Cleaning

- Modern agricultural radial tire
- The shape and angle of the lugs provide good traction and low slippage with excellent power transmission to the ground
- Wide footprint area for improved stability and minimum ground pressure
- Superior self-cleaning features that allow for a quick change from field operations to road usage
- Low wear compound for longer tire life



GENESIS

TRA: R-1

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ± 2.5%	Rolling Circumference mm ± 2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Static	10	20	25	30	40	50	65
210/95R16 (7.50R16)	106A8/106B	TL	32.0	7.00	795	215	368	2373	240	2185	1425	1170	1055	1020	950	950	-
260/70R16	109A8/109B	TL	31.0	8.00	767	250	345	2293	240	2370	1545	1270	1140	1100	1030	1030	-
280/70R16	112A8/112B	TL	32.0	9.00	787	273	357	2350	240	2575	1680	1380	1240	1200	1120	1120	-
210/95R18 (7.50R18)	108A8/108B	TL	32.0	7.00	849	215	393	2542	240	2300	1500	1230	1110	1070	1000	1000	-
280/70R18	114A8/114B	TL	32.0	9.00	849	273	385	2542	240	2710	1770	1450	1310	1260	1180	1180	-
210/95R20 (7.50R20)	110A8/110B	TL	32.0	7.00	895	215	413	2686	240	2440	1590	1300	1180	1135	1060	1060	-
280/70R20	116D	TL	32.0	9.00	899	273	412	2698	240	2875	1875	1540	1480	1440	1370	1310	1250
300/70R20	120A8/120B	TL	33.0	9.00	948	290	427	2840	240	3220	2100	1720	1550	1500	1400	1400	-
320/70R20	123A8/123B	TL	34.0	10.00	985	316	450	2947	240	3565	2325	1910	1720	1660	1550	1550	-
360/70R20	129A8/129B	TL	41	W11	1054	357	-	-	240	4250	2775	2280	2050	1980	1850	1850	-
380/70R20	132A8/132B	TL	42	W12	1074	370	-	-	240	4600	3000	2460	2220	2140	2000	2000	-
420/65R20	135D/138A8	TL	38	13.00	1060	415	459	3105	240	5450	3270	2680	2580	2510	2360	2290	2180
320/85R32 (12.4R32)	126A8/126B	TL	36.0	10.00	1354	311	623	4063	160	3910	2550	2090	1890	1820	1700	1700	-
320/85R36 (12.4R36)	128A8/128B	TL	36.0	10.00	1448	313	667	4368	160	4140	2700	2215	2000	1925	1800	1800	-
340/85R36 (13.6R36)	132A8/132B	TL	37.0	11.00	1489	357	680	4489	160	4600	3000	2460	2220	2140	2000	2000	-
340/85R38 (13.6R38)	133A8/133B	TL	37.0	11.00	1540	353	711	4645	160	4740	3090	2535	2290	2205	2060	2060	-