

GRASS KING FLOTATION



High Speed



Field Protection



Reduced Soil Compaction



Comfort

- Wide contact area for even ground pressure distribution at low inflation pressure
- 65 km/h approval
- Superior ground protection on grassland and other surfaces
- Well balanced pattern design for a great variety of applications
- Suitable for municipality vehicles, two-axle mower and multipurpose transporter
- Excellent drive comfort even on long distances

GRASS KING FLOTATION

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ± 2.5%	Rolling Circumference mm ± 2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
31x15.50R15	122B	TL	19.0	13LB	792	391	355	2378	280	3450	2700	2475	2370	2265	2040	1500	-
33x15.50R15	126B	TL	20.0	13LB	840	394	417	2481	310	3910	3060	2805	2685	2570	2310	1700	-
19.0/45R17	137D	TL	18.0	16.00	858	477	396	2578	400	5290	4140	3795	3630	3470	3130	2780	2300
425/55R17	137D	TL	20.0	13.00	890	421	398	2670	350	5290	4140	3795	3630	3470	3130	2780	2300
440/50R17	135D	TL	22.0	13.00	852	433	-	-	360	5010	3920	3600	3440	3290	2965	2640	2180
500/50R17	146D	TL	18.0	16.00	924	492	415	2773	400	6900	5400	4950	4740	4530	4080	3630	3000
480/50R20	140D	TL	20.0	16.00	997	478	448	2997	300	5750	4500	4125	3950	3775	3400	3025	2500
500/45R22.5	146D	TL	20.0	16.00	1028	493	466	3097	400	6900	5400	4950	4740	4530	4080	3630	3000