





GSR1 Regional / Steer Tyre

New steer tyre engineered with innovative GOODRIDE's latest technology for local and regional operations.

- Advanced 5-Rib tread provides even wear and remarkable handling.
- ▶ Special designed tread pitches ensure low external noise.
- Tread sipes with straight tread grooves guarantee excellent water drainage and outstanding wet traction.
- Computer designed tyre casing promises good footprint to extend tyre life.





Size	LR/PR	Service Index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure				4 H)	16 of		NDISE (dB)
							Sir (kg)	ngle (kpa)	(kg) Di	iai (kpa)		2 1/2		MAISE (80)
385/65R22.5	J/18	158L(160K)	15.0	11.75	1072	389	4250	850	_		С	С	2	71
315/70R22,5	L/20	156/150L	15.0	9,00	1020	312	3750	900	3350	900	C	С	2	71
295/80R22.5	J/18	154/149M	16.0	9.00	1044	298	3550	900	3250	900	D	С	2	71
315/80R22.5	J/18	154/151M(156/150L)	16.0	9.00	1076	312	3750	830	3450	830	С	С	2	71