

# LOG STOMPER-METRIC GRIP



- The high flotation forestry tires, with large ground contact area, low-pressure ratio on the ground and less damage to soil and sapling.
- Tread bars at certain angle give good self-cleaning capacity, excellent traction and slide slippage-proof.
- Its carcass design with steel belt protection gives the best resistance to punctures.
- Deep tread design and cut-resistant tread compound give extended tire life.



**OEM FITMENT**



LOG STOMPER-METRIC GRIP									TRA: LS-2	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity	
									Speed 40km/h	
									Inflation KPa	Load kg
*750/55-26.5	20	TT/TL	53.2	24.00	1485	750	685	4565	500	7300
	24								600	8500



LOG STOMPER-METRIC GRIP									TRA: LS-2	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity	
									Speed 40km/h	
									Inflation KPa	Load kg
*600/65-34	16	TT/TL	50.0	DW20B, DW18L	1650	600	759	4823	240	4125
	20	TL							320	4875

LOG STOMPER-METRIC GRIP							TRA: LS-2	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Load Capacity	
							Speed 40km/h	
							Inflation KPa	Load kg
*700/55-34	16	TT/TL	50.0	DW24B	1650	700	240	4625
	20	TT/TL					320	5300
	24	TL					400	6500



\*: With Steel Belt