



- Excellent traction for ON/OFF drive axle application
- Aggressive and optimum self-cleaning tread with lateral grooves provides remarkable performance in all weather conditions both on and off the roads



- : Recommendable
- : Available

MD738/MD738A

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single			Dual				
							(kg)	(lbs)	(kPa) (psi)	(kg)	(lbs)	(kPa) (psi)		
🇹🇭 9.5R17.5(MD738)	G/14	129/127L	16.5	6.75	842	240	1850	4080	750	109	1750	3860	750	109
🇹🇭 9.5R17.5(MD738)	H/16	143/141J	16.5	6.75	842	240	2725	6005	875	128	2575	5675	875	128
🇨🇳 9.5R17.5(MD738A)	G/14	129/127L	15.0	6.75	842	240	1850	4080	750	109	1750	3860	750	109
🇨🇳 9.5R17.5(MD738A)	H/16	143/141J	15.0	6.75	842	240	2725	6005	875	128	2575	5675	875	128
🇹🇭 215/75R17.5(MD738)	H/16	135/133J	15.0	6.00	767	211	2180	4805	850	123	2060	4540	850	123
🇹🇭 235/75R17.5(MD738)	G/14	132/130M	16.0	6.75	797	233	2000	4410	775	112	1900	4190	775	112
🇹🇭 235/75R17.5(MD738)	H/16	143/141J	16.0	6.75	797	233	2725	6005	875	128	2575	5675	875	128
🇹🇭 11R22.5(MD738)	G/14	144/142L	20.6	8.25	1065	279	2800	6175	720	105	2650	5840	720	105
🇹🇭 11R22.5(MD738)	H/16	148/145L	20.6	8.25	1065	279	3150	6940	850	123	2900	6390	850	123
🇹🇭 12R22.5(MD738)	J/18	152/149L	20.6	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
🇨🇳 275/70R22.5(MD738)	H/16	148/145J	18.0	8.25	964	276	3150	6940	900	130	2900	6395	900	130
🇹🇭 295/80R22.5(MD738)	H/16	150/147L	20.6	9.00	1050	298	3350	7390	830	120	3075	6780	830	120
🇨🇳 295/80R22.5(MD738)	J/18	152/149L	20.6	9.00	1050	298	3550	7830	900	131	3250	7160	900	131
🇨🇳 11R24.5(MD738)	G/14	146/143L	22.6	8.25	1116	279	3000	6610	720	105	2725	6005	720	105
🇨🇳 11R24.5(MD738)	H/16	149/146L	22.6	8.25	1116	279	3250	7160	830	120	3000	6610	830	120

🇨🇳 Made in China 🇹🇭 Made in Thailand