

MUD LEGEND SL378



Benefits and Features

- The aggressive tread design is engineered to provide strong biting edges
- The staggered, off-center tread blocks provide increased traction while enhancing road performance
- Built to handle rugged terrains anywhere and to take you on extreme adventures
- Robust shoulder design helps to minimizing cuts



M+S

Rim Size	15 - 18
Series	60 - 85
Speed Rating	Q

MUD LEGEND SL378

Rim (inch)	Size	LR/PR	Service Index	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Load (kg)	Max. Air Pressure (kpa)	TT/TL	Rim (inch)	Size	LR/PR	Service Index	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Load (kg)	Max. Air Pressure (kpa)	TT/TL
15"	31×10.50R15LT	C/6PR	109Q	8.5J	268	781	1030	350	TL	16"	LT265/75R16	E/10PR	123/120Q	7.5J	267	810	1550/1400	550	TL
	33×12.50R15LT	C/6PR	108Q	10.0J	318	832	1000	250	TL		LT285/75R16	E/10PR	126/123Q	8.0J	286	840	1700/1550	550	TL
	LT215/75R15	C/6PR	100/97Q	6.0J	216	703	800/730	350	TL		LT235/85R16	E/10PR	120/116Q	6.5J	235	812	1380/1260	550	TL
	LT235/75R15	C/6PR	104/101Q	6.5J	235	739	900/825	350	TL		LT265/65R17	E/10PR	120/117Q	8.0J	272	775	1400/1285	550	TL
	LT235/75R15	D/6PR	110/107Q	6.5J	235	739	1060/975	450	TL		LT245/70R17	E/10PR	119/116Q	7.0J	248	776	1360/1250	550	TL
16"	LT245/70R16	E/10PR	118/115Q	7.0J	248	750	1320/1215	550	TL	LT265/70R17	E/10PR	121/118Q	8.0J	272	810	1450/1320	550	TL	
	LT265/70R16	E/10PR	121/118Q	8.0J	272	784	1450/1320	550	TL	LT285/70R17	E/10PR	121/118Q	8.5J	292	832	1450/1320			
	LT245/75R16	E/10PR	120/116Q	7.0J	248	780	1380/1260			18"	LT265/60R18	E/10PR	119/116Q	8.0J	272	775	1360/1250		

● Made in China

