

MULTI SURFACE



Enhanced
Sidewall



Excellent
Traction

- Advance design with open pattern groove, which can provide excellent traction performance
- High degree of saturation pattern design, with better and reliable worn resistance
- Optimized design of the sidewall, in order to offering excellent resistance of both aging and flexure



MULTI SURFACE

TRA: R-4

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ±2.5%	Rolling Circumference mm ±2.5%	Inflation Pressure KPa	Load Capacity Kg						
										Speed Km/h						
405/70R18 (16/70R18)	141B	TL	26.0	13.00	1025	402	468	3064	400	5920	3220	2810	2730	2680	2575	2575
405/70R20 (16/70R20)	149A8/149B	TL	26.0	13.00	1076	403	488	3224	400	7475	4060	3540	3445	3380	3250	3250
460/70R24 (17.5LR24)	159A8/159B	TL	28.0	15.00	1250	463	562	3701	400	10060	5470	4770	4640	4550	4375	4375
500/70R24 (19.5LR24)	164A8/164B	TL	28.0	16.00	1310	503	592	3928	400	11500	6250	5450	5300	5200	5000	5000