

RUGGED LEGEND SL339



Benefits and Features

Optimized tread design with wide tread large block and variable pitch pattern

Two-wide circumferential zigzag grooves and Center cross pattern grooves with stone ejectors Provide superb off-road traction throughout the tyre's wear life with stone ejectors to help prevent stone drilling

Aggressive sidewall design offer customization with a distinct look on each side of the tyre

Open shoulder design and wide lateral grooves ensure excellent driving performance of the tyre



M+S

Rim Size	15 - 20
Series	50 - 85
Speed Rating	Q - T

RUGGED LEGEND SL339

Rim (inch)	Size	Service Index	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Load (kg)	Max. Air Pressure (kpa)	UTQG	TT/TL	Rim (inch)	Size	LR/PR	Service Index	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Load (kg)	Max. Air Pressure (kpa)	TT/TL
15"	235/75R15	109S	6.5J	235	733	1030	350	500 A A	TL	15"	LT215/75R15	D/8PR	106/103Q	6.0J	223	719	950/875	450	TL
16"	245/70R16 XL	111S	7.0J	248	750	1090	350	500 A A	TL	16"	LT235/75R15	D/8PR	110/107Q	6.5J	233	739	1060/975	450	TL
	255/70R16	111T	7.5J	260	764	1090	300	500 A A	TL		31*10.50R15LT	C/6PR	109Q	8.5J	268	775	1030	350	TL
	265/70R16	112S	8.0J	272	778	1120	300	500 A A	TL		33*12.50R15LT	C/6PR	108Q	10.0J	318	826	1000	250	TL
	275/70R16	114S	8.0J	279	792	1180	300	500 A A	TL	16"	LT245/70R16	E/10PR	118/115Q	7.0J	248	750	1320/1215	550	TL
17"	245/65R17	107S	7.0J	248	750	975	300	500 A A	TL		LT265/70R16	E/10PR	121/118Q	8.0J	272	778	1450/1320	550	TL
	265/65R17	112S	8.0J	272	776	1120	300	500 A A	TL		LT245/75R16	E/10PR	120/116Q	7.0J	248	774	1380/1260	550	TL
18"	265/60R18	110T	8.0J	272	775	1060	300	500 A A	TL		LT265/75R16	E/10PR	123/120Q	7.5J	267	804	1550/1400	450	TL
	285/60R18	116T	8.5J	292	799	1250	300	500 A A	TL		LT285/75R16	E/10PR	126/123Q	8.0J	286	834	1700/1550	550	TL
	265/65R18	114T	8.0J	272	801	1180	300	500 A A	TL		LT235/65R16	E/10PR	120/116Q	6.5J	235	806	1380/1260	550	TL
20"	265/50R20 XL	111T	8.5J	277	774	1090	350	500 A A	TL	17"	LT285/65R17	E/10PR	120/117Q	8.0J	272	776	1400/1285	550	TL
	275/55R20 XL	117T	8.5J	284	810	1285	350	500 A A	TL		LT245/70R17	E/10PR	119/116Q	7.0J	248	776	1360/1250	550	TL
											LT265/70R17	E/10PR	123/120Q	8.0J	272	804	1550/1400	550	TL
											LT285/70R17	E/10PR	126/123Q	8.5J	292	832	1700/1550	550	TL
											LT285/65R17	E/10PR	121/118Q	8.5J	292	802	1450/1320	550	TL

Made in Thailand

