

ZUPERACE SA-57



Benefits and Features

- New generation of directional Ultra High Performance tyre
- Circumferential V-grooves ensure outstanding water drainage
- Strong center ribs provides remarkable handling while steering
- Improved SILICA compounding enhance the wet and dry grip



M+S

Rim Size	14 - 24
Series	30 - 65
Speed Rating	H - W

ZUPERACE SA-57

Rim (inch)	Size	Service Index	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Load (kg)	Max. Air Pressure (kpa)	UTQG	TT/TL
14"	185/60R14	82H	5.5J	189	578	475	300	460 A A	TL
	175/65R14	82H	5.0J	177	584	475	300	460 A A	TL
	185/65R14	86H	5.5J	189	596	530	300	460 A A	TL
15"	195/50R15	82V	6.0J	201	577	475	300	460 A A	TL
	185/55R15	82V	6.0J	194	585	475	300	460 A A	TL
	195/55R15	85V	6.0J	201	595	515	300	460 A A	TL
	185/60R15	84H	5.5J	189	603	500	300	460 A A	TL
	195/60R15	88V	6.0J	201	615	560	300	460 A A	TL
	195/65R15	91V	6.0J	201	635	615	300	460 A A	TL
16"	205/45ZR16 XL	87W	7.0J	206	590	545	350	460 A A	TL
	195/50R16	84V	6.0J	201	602	500	300	460 A A	TL
	205/50R16	87W	6.5J	214	612	545	300	460 A A	TL
	225/50R16	92W	7.0J	233	632	630	300	460 A A	TL
	205/55R16 XL	94W	6.5J	214	632	670	350	460 A A	TL
	215/55R16 XL	97W	7.0J	226	642	730	350	460 A A	TL
	225/55R16 XL	99W	7.0J	233	654	775	350	460 A A	TL
	235/60R16	100H	7.0J	240	688	800	300	460 A A	TL
17"	205/40ZR17 XL	84W	7.5J	212	596	500	350	460 A A	TL
	215/40ZR17 XL	87W	7.5J	218	604	545	350	460 A A	TL
	245/40ZR17 XL	95W	8.5J	248	628	690	350	460 A A	TL
	205/45ZR17 XL	88W	7.0J	206	616	560	350	460 A A	TL
	215/45ZR17 XL	91W	7.0J	213	626	615	350	460 A A	TL
	225/45ZR17 XL	94W	7.5J	225	634	670	350	460 A A	TL
	235/45ZR17 XL	97W	8.0J	236	644	730	350	460 A A	TL
	205/50R17 XL	93W	6.5J	214	638	650	350	460 A A	TL
	215/50R17 XL	95W	7.0J	226	648	690	350	460 A A	TL
	225/50R17 XL	98W	7.0J	233	658	750	350	460 A A	TL
	215/55R17 XL	98W	7.0J	226	668	750	350	460 A A	TL
	225/55R17 XL	101W	7.0J	233	680	825	350	460 A A	TL
	235/55R17 XL	103W	7.5J	245	690	875	350	460 A A	TL
18"	265/35ZR18 XL	97W	9.5J	271	643	730	350	460 A A	TL
18"	225/40ZR18 XL	92W	8.0J	230	637	630	350	460 A A	TL
	235/40ZR18 XL	95W	8.5J	241	645	690	350	460 A A	TL
	245/40ZR18 XL	97W	8.5J	248	653	730	350	460 A A	TL
	225/45ZR18 XL	95W	7.5J	225	659	690	350	460 A A	TL
	235/45ZR18 XL	98W	8.0J	236	669	750	350	460 A A	TL
	245/45ZR18 XL	100W	8.0J	243	677	800	350	460 A A	TL
	225/50R18	95W	7.0J	233	683	690	300	460 A A	TL
	235/50R18 XL	101W	7.5J	245	693	825	350	460 A A	TL
	255/55R18 XL	109V	8.0J	265	737	1030	350	460 A A	TL
	265/60R18	110V	8.0J	272	775	1060	300	460 A A	TL
19"	215/35ZR19 XL	85W	7.5J	218	633	515	350	460 A A	TL
	225/35ZR19 XL	88W	8.0J	230	641	560	350	460 A A	TL
	245/45ZR19 XL	102W	8.0J	243	703	850	350	460 A A	TL
	255/45ZR19 XL	104W	8.5J	255	713	900	350	460 A A	TL
20"	205/30ZR20	80W	7.5J	212	632	450	350	460 A A	TL
	215/30ZR20	82W	7.5J	218	638	475	350	460 A A	TL
	245/30ZR20 XL	90W	8.5J	248	656	600	350	460 A A	TL
	275/40ZR20 XL	106W	9.5J	278	728	950	350	460 A A	TL
	255/45R20 XL	105V	8.5J	255	738	925	350	460 A A	TL
	275/45R20 XL	110V	9.0J	273	756	1060	350	460 A A	TL
	265/50R20 XL	111V	8.5J	277	774	1090	350	460 A A	TL
	285/50R20	112V	9.0J	297	794	1120	300	460 A A	TL
	275/55R20 XL	117V	8.5J	284	810	1285	350	460 A A	TL
	275/60R20 XL	119V	8.0J	279	838	1360	350	460 A A	TL
22"	265/35R22 XL	102V	9.5J	271	745	850	350	460 A A	TL
	285/35R22 XL	106V	10.0J	290	759	950	350	460 A A	TL
	265/40R22 XL	106V	9.5J	271	771	950	350	460 A A	TL
	305/40R22 XL	114V	11.0J	313	803	1180	350	460 A A	TL
	305/45R22 XL	118V	10.0J	303	833	1320	350	460 A A	TL
24"	295/35R24 XL	110V	10.5J	301	816	1060	350	460 A A	TL

● Made in China ● Made in Thailand

