

SC328



Benefits and Features

- Wide four ribs improve miles to tread life
- Zig-zag grooves offers enhanced traction on wet road
- Combination construction of polyester casing and steel belts provide outstanding durability



M+S

Rim Size 12 - 16
Series 60 - 75
Speed Rating Q - T

SC328

Rim (inch)	Size	LR/PR	Service Index	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Load (kg)	Max. Air Pressure (kpa)	TT/TL	Rim (inch)	Size	LR/PR	Service Index	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Load (kg)	Max. Air Pressure (kpa)	TT/TL
12"	155R12C	C/6PR	83/81Q	4.5B	157	550	487/462	350	TL	15"	215/70R15C	D/8PR	109/107R	6.5J	221	683	1030/975	475	TL
	155R12C	D/8PR	88/86Q	4.5B	157	550	560/530	450	TL		225/70R15C	D/8PR	112/110R	6.5J	228	697	1120/1060	450	TL
13"	155R13C	D/8PR	90/88S	4.5B	157	578	600/560	450	TL	16"	175R16C	C/6PR	98/96Q	5.0J	178	684	750/710	375	TL
	165R13C	C/6PR	91/89Q	4.5B	167	596	615/580	375	TL		215/60R16C	D/8PR	108/106T	6.5J	221	664	1000/950	475	TL
	165R13C	D/8PR	94/92Q	4.5B	165	594	670/650	450	TL		195/65R16C	D/8PR	104/102T	6.0J	201	660	900/850	475	TL
	175R13C	D/8PR	97/95Q	5.0B	178	609	730/690	450	TL		205/65R16C	D/8PR	107/105T	6.0J	209	672	975/925	475	TL
14"	165/70R13C	C/6PR	88/86S	5.0B	170	562	560/530	375	TL	15"	215/65R16C	D/8PR	109/107R	6.5J	221	686	1030/975	475	TL
	185R14C	D/8PR	102/100Q	5.5J	188	650	850/800	450	TL		225/65R16C	D/8PR	112/110R	6.5J	228	698	1120/1060	475	TL
	195R14C WSW	D/8PR	106/104Q	5.5J	198	666	950/900	450	TL		235/65R16C	D/8PR	115/113R	7.0J	240	712	1215/1150	475	TL
	205R14C	D/8PR	109/107R	6.0J	208	686	1030/975	450	TL		235/65R16C	F/12PR	121/119R	7.0J	240	712	1450/1360	575	TL
	215R14C	D/8PR	112/110Q	6.0J	218	700	1120/1060	450	TL		215/70R16C	C/6PR	108/106T	6.5J	221	708	1000/950	375	TL
	165/70R14C	C/6PR	89/87R	5.0J	170	588	580/545	375	TL		215/70R16C	E/10PR	113/111Q	6.5J	221	708	1150/1090	585	TL
	205/70R14C	C/6PR	102/100R	6.0J	209	644	850/800	375	TL		175/75R16C	D/8PR	101/99Q	5.0J	177	668	825/775	475	TL
	215/75R14C	D/8PR	112/110Q	6.0J	216	678	1120/1060	475	TL		195/75R16C	D/8PR	107/105R	5.5J	196	698	975/925	475	TL
15"	185R15C	D/8PR	103/102R	5.5J	188	674	875/850	450	TL	16"	195/75R16C	E/10PR	110/108R	5.5J	196	698	1060/1000	525	TL
	195R15C	D/8PR	106/104R	5.5J	198	690	950/900	450	TL		205/75R16C	D/8PR	110/108Q	5.5J	203	714	1060/1000	475	TL
	215R15C	D/8PR	112/110Q	6.0J	218	724	1120/1060	450	TL		205/75R16C	E/10PR	113/111R	5.5J	203	714	1150/1090	525	TL
	205/65R15C	C/6PR	102/100T	6.0J	209	647	850/800	375	TL		205/75R16C	F/12PR	116/114R	5.5J	203	714	1250/1180	575	TL
	195/70R15C	D/8PR	104/102R	6.0J	201	655	900/850	450	TL		215/75R16C	D/8PR	113/111Q	6.0J	216	728	1150/1090	475	TL
	205/70R15C	D/8PR	106/104R	6.0J	209	669	950/900	475	TL		215/75R16C	E/10PR	116/114R	6.0J	216	728	1250/1180	525	TL

● Made in China ● Made in Thailand WSW White Sidewall Tyre (WSW)

