

SUPER EXTRA WOODLAND PREMIUM



- This tire has premium wide and deep "herringbone" tread bars with 45° angle, a flat profile plus kevlar or steel belt protection on sidewall and tread, so you end up with this ultimate forestry tire designed to stand up to the most tough working conditions. This tire is your only choice.



Durability

OEM FITMENT



SUPER EXTRA WOODLAND PREMIUM									TRA: LS-1	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity Speed 30km/h	
									Inflation KPa	Load kg
*18.4-38	16	TT/TL	41.0	W16A, DD16, W15L	1763	457	-	-	300	4375

SUPER EXTRA WOODLAND PREMIUM									TRA: LS-2	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity Speed 30km/h	
									Inflation KPa	Load kg
*16.9-30	16	TT	53.0	W15L, DW15A, W14L, DW14A	1488	414	694	4467	310	3250
*18.4-26	16	TT/TL	50.5	DW16A	1450	455	652	4314	280	3450
*18.4-30	16	TT/TL	50.5	DW16A	1557	483	727	5005	280	3650
*18.4-34	16	TT/TL	51.0	DW16A, DW15A	1664	447	780	4986	280	3875
20.5-25	16	TL	50.5	17.00/2.0 (1.7)	1450	427	-	-	225	4500
	20								275	5000
*20.8-38	16	TT/TL	50.5	W18A, DD18, DW18A	1834	528	860	6048	250	4750

SUPER EXTRA WOODLAND PREMIUM									TRA: LS-2	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity Speed 30km/h	
									Inflation kPa	Load kg
*23.1-26	16	TT/TL	63.5	DW20B	1628	584	726	5076	240	4500
	20								280	4875
*24.5-32	16	TT/TL	59.5	DH21, DH21H	1806	587	-	-	210	5000
	20	TT/TL							280	6000
	24	TL							340	6700
28L-26	16	TT	57.0	DW25B	1676	683	-	-	210	4750
	18								220	4875
*30.5L-32	16	TT	66.5	DH27, DH27H	1844	732	-	-	170	5300
	20	TT/TL							210	6000
	26	TT							280	7100
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity Speed 40km/h	
									Inflation kPa	Load kg
 *320/85-24 (*12.4-24)	14	TL	42.0	W11	1178	311	-	-	240	1750
*380/85-24	14	TL	47.5	W12	1260	380	580	3729	240	2300
*380/85-28	14	TL	47.5	W12	1365	380	-	-	240	2430
*420/85-28	14	TL	53.5	W15L, W14L	1432	428	666	4231	240	2800

*:With Steel Belt