

SL369 A/T



Benefits and Features

Wide tread and multi-stepped grooves increase surface area of tread to enhance traction on both on and off roads

Zig-zag grooves efficient water drainage and enhanced traction on wet road

Large tread blocks help enhanced stability and handling with less noise on highway

Aggressive sidewall protectors increase off-road bite and prevent damage from sidewall cut and abrasions



M+S

Rim Size	14 - 20
Series	45 - 85
Speed Rating	Q - V

SL369 A/T

Rim (inch)	Size	Service Index	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Load (kg)	Max. Air Pressure (kpa)	UTQG	TT/TL
14"	175/70R14	84T	5.0J	177	602	500	300	440 A A	TL
	175/80R14	88T	5.0J	177	636	560	300	440 A A	TL
	P215/75R14	100T	6.0J	216	678	800	300	500 A A	TL
15"	205/65R15	94H	6.0J	209	647	670	300	500 A A	TL
	205/70R15	96H	6.0J	209	669	710	300	500 A A	TL
	225/70R15	100T	6.5J	228	697	800	300	500 A A	TL
	235/70R15	103S	7.0J	240	711	875	300	500 A A	TL
	265/70R15	112T	8.0J	272	753	1120	300	500 A A	TL
	P215/75R15	100S	6.0J	216	703	800	300	500 A A	TL
	235/75R15 XL	109S	6.5J	235	733	1030	350	500 A A	TL
	245/75R15	108T	7.0J	248	749	1000	300	500 A A	TL
16"	205/60R16	92H	6.0J	209	652	630	300	500 A A	TL
	235/60R16	100T	7.0J	240	688	800	300	500 A A	TL
	215/70R16	100S	6.5J	221	708	800	300	500 A A	TL
	225/70R16	103S	6.5J	228	722	875	300	500 A A	TL
	235/70R16	106S	7.0J	240	736	950	300	500 A A	TL
	245/70R16 XL	111S	7.0J	248	750	1090	350	500 A A	TL
	255/70R16	111T	7.5J	260	764	1090	300	500 A A	TL
	265/70R16	112S	8.0J	272	778	1120	300	500 A A	TL
	275/70R16	114S	8.0J	279	792	1180	300	500 A A	TL
	225/75R16 XL	106S	6.0J	223	744	1000	350	500 A A	TL
	235/75R16 XL	112S	6.5J	235	758	1120	350	500 A A	TL
	245/75R16	111S	7.0J	248	774	1090	300	500 A A	TL
	265/75R16	116S	7.5J	267	804	1250	300	500 A A	TL
	205/80R16 XL	104S	5.5J	203	734	900	350	440 A A	TL
	215/80R16 XL	107S	6.0J	216	750	975	350	440 A A	TL
17"	225/65R17	102T	6.5J	228	724	850	300	500 A A	TL
	235/65R17	104S	7.0J	240	738	900	300	500 A A	TL
	245/65R17	107S	7.0J	248	750	975	300	500 A A	TL
	255/65R17	110T	7.5J	260	764	1060	300	500 A A	TL
	265/65R17	112S	8.0J	272	776	1120	300	500 A A	TL
	225/70R17 XL	108S	6.5J	228	748	1000	350	500 A A	TL
	245/70R17	110T	7.0J	248	776	1000	300	500 A A	TL
	255/70R17	112T	7.5J	260	790	1120	300	500 A A	TL
	265/70R17	115T	8.0J	272	804	1215	300	500 A A	TL
	285/70R17	117T	8.5J	292	832	1285	300	500 A A	TL
	245/75R17	112T	7.0J	248	800	1120	300	500 A A	TL
	255/75R17	115T	7.0J	255	814	1215	300	500 A A	TL
18"	265/60R18	110T	8.0J	272	775	1060	300	500 A A	TL
	285/60R18	116T	8.5J	292	799	1250	300	500 A A	TL
	265/65R18	114T	8.0J	272	801	1180	300	500 A A	TL
	275/65R18	116T	8.0J	279	815	1250	300	500 A A	TL
20"	275/45R20 XL	110H	9.0J	273	756	1060	350	500 A A	TL
	265/50R20 XL	111T	8.5J	277	774	1090	350	500 A A	TL
	285/50R20 XL	116V	9.0J	297	794	1250	350	500 A A	TL
	275/55R20	113S	8.5J	284	810	1150	300	500 A A	TL
	275/60R20	115T	8.0J	279	838	1215	300	500 A A	TL

● Made in China ● Made in Thailand CFW Outline White Letters (OWL)

