

SUPER LOGGER



- Its 23° angle tread bars give superior traction.
- The rim flange protector is a special feature to protect the sidewall against snags and branches.
- Carcass design with steel belt protection produces a longer tire life.



SUPER LOGGER									TRA: LS-2	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity	
									Speed 30km/h	
									Inflation KPa	Load kg
*23.1-26	16	TT/TL	53.5	DW20B	1632	587	726	5026	240	4500
*23.1-34	16	TT	53.5	DW20B	1835	587	898	5337	240	5000
*24.5-32	16	TT	54.5	DH21, DH21H	1831	622	-	-	210	5000
	20	TT/TL							280	6000
*28L-26	16	TT	57.0	DW25B	1644	714	-	-	210	4750
	20	TT/TL							240	5150
*30.5L-32	20	TT/TL	62.5	DH27, DH27H	1868	775	-	-	210	6000
	26	TL							280	7100
	32	TL							340	8500
*DH35.5L-32	20	TT/TL	63.5	DH31, DH31H	1935	878	-	-	170	7300
	26	TL							240	8750
	32	TL							310	9750
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm±2.5%	Rolling Circumference mm±2.5%	Load Capacity	
									Speed 40km/h	
									Inflation KPa	Load kg
*700/70-34	16	TT/TL	50.0	DW20B	1844	700	843	5956	240	5600
	20	TL							320	6500
	24	TL							400	7500

*: With Steel Belt