

## ST313



## Benefits and Features

- Applicable for mini-bus, van and commercial light trucks
- Strong sidewall design enables high durability and fights off cuts and abrasion in city roads
- Triply polyester belts plies creates strength bearing heavy loads with superior stability



M+S

|              |         |
|--------------|---------|
| Rim Size     | 15 - 16 |
| Series       | 75 - 85 |
| Speed Rating | L - R   |

## ST313

| Rim (inch) | Size       | LR/PR  | Service Index | Standard Rim | Section Width (mm) | Overall Diameter (mm) | Max. Load (kg) | Max. Air Pressure (kpa) | TT/TL | Rim (inch) | Size        | LR/PR  | Service Index | Standard Rim | Section Width (mm) | Overall Diameter (mm) | Max. Load (kg) | Max. Air Pressure (kpa) | TT/TL |
|------------|------------|--------|---------------|--------------|--------------------|-----------------------|----------------|-------------------------|-------|------------|-------------|--------|---------------|--------------|--------------------|-----------------------|----------------|-------------------------|-------|
| 15"        | 6.50R15LT  | E/10PR | 107/105N      | 5.5F         | 180                | 730                   | 975/925        | 560                     | TT/TL | 16"        | 7.50R16LT   | G/14PR | 122/121L      | 6.0G         | 220                | 808                   | 1500/1450      | 740                     | TT/TL |
|            | 7.00R15LT  | E/10PR | 110/106N      | 5.5F         | 200                | 750                   | 1060/950       | 560                     | TT/TL |            | 205/75R16C  | F/12PR | 116/114R      | 5.5J         | 203                | 714                   | 1250/1180      | 575                     | TL    |
|            | 195/75R15C | F/12PR | 109/107L      | 5.5J         | 196                | 673                   | 1030/975       | 600                     | TL    |            | 185/85R16LT | F/12PR | 111/109L      | 5.0J         | 184                | 720                   | 1090/1030      | 600                     | TL    |
|            | 195/85R15C | F/12PR | 113/111L      | 5.5J         | 196                | 713                   | 1150/1090      | 600                     | TL    |            | 195/85R16LT | F/12PR | 114/112L      | 5.5J         | 196                | 738                   | 1180/1120      | 600                     | TL    |
| 16"        | 6.50R16LT  | E/10PR | 108/107N      | 5.5F         | 185                | 750                   | 1000/975       | 560                     | TT/TL |            | 205/85R16LT | F/12PR | 117/115L      | 5.5J         | 203                | 754                   | 1285/1215      | 600                     | TL    |
|            | 7.00R16LT  | F/12PR | 117/116N      | 5.5F         | 200                | 775                   | 1285/1250      | 670                     | TT/TL |            | 205/85R16LT | F/12PR | 117/115L      | 5.5J         | 203                | 754                   | 1285/1215      | 600                     | TL    |
|            | 7.00R16LT  | F/12PR | 117/116N      | 5.5F         | 200                | 775                   | 1285/1250      | 670                     | TT/TL |            |             |        |               |              |                    |                       |                |                         |       |

● Made in China    ● Made in Thailand

